

# INTEGRATED CE S BUS

**Sales Proposal For:** 

**Galveston ISD** 

Presented By:

**LONGHORN BUS SALES** 

Prepared For:

Galveston ISD Mike Praker 3101 83rd st. Galveston, TX 77554-(409)740 - 1208

Presented By: LONGHORN BUS SALES LINDA BLUME 9100 N LOOP E HOUSTON TX 77029 -(713)631-9306

Reference ID: 4-77P DSL 3PT

Thank you for the opportunity to provide you with the following quotation on a new IC Corporation vehicle. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

> **Model Profile** 2022 INTEGRATED CE S BUS (PB105)

APPLICATION:

MISSION:

School Transportation

Requested GVWR: 29800. Calc. GVWR: 31000

Calc. Start / Grade Ability: 26.96% / 1.85% @ 55 MPH

Calc. Geared Speed: 79.2 MPH

**DIMENSION:** Wheelbase: 276.00, CA: N/A, Axle to Frame: 166.00

{Cummins B6.7 240} EPA 2021, 240HP @ 2400 RPM, 560 lb-ft Torque @ 1600 RPM, 2600 RPM **ENGINE, DIESEL:** 

Governed Speed, 240 Peak HP (Max), School Bus Only

TRANSMISSION, AUTOMATIC: {Allison 2500 PTS} 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less

PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus

Omit Item (Clutch & Control) CLUTCH:

**AXLE, FRONT NON-DRIVING:** {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity

**AXLE, REAR, SINGLE:** {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends Gear Ratio: 6.14 (2) 11R22.5 Load Range H X MULTI ENERGY Z (MICHELIN), 501 rev/mile, 75 MPH, All-Position TIRE, FRONT: (4) 11R22.5 Load Range H X MULTI ENERGY Z (MICHELIN), 501 rev/mile, 75 MPH, All-Position TIRE, REAR:

SUSPENSION, REAR, AIR, SINGLE: {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers

Cab schematic 100NB PAINT:

Location 1: 4421, School Bus Yellow (Std)

Chassis schematic N/A

| <u>Code</u><br>PB10500 | <u>Description</u> Base Chassis, Model INTEGRATED CE S BUS with 276.00 Wheelbase, N/A CA, and 166.00 Axle to Frame.  |
|------------------------|--|
| BODY PLANS             |  |
| 47AMG                  | BODY, BUS Conventional; 78" Headroom, 34'11" Body Length, +9 Section Rear, 78 Passenger, 276 WB  |
|                        | Includes : NOTE: Body Mandates Overall Vehicle Length of Greater than 40 Feet  |
| 50UCJ                  | BODY PLAN, NON-SPECIAL NEEDS Conventional; 34' 11" Body Length, +9 Section Rear, 77 Passenger, 276" WB, DX9386A000   |
| 49001                  | BODY PLAN, APPROVED VARIATION Number 001   |
| ENGINE                 |  |
| 12ERS                  | ENGINE, DIESEL {Cummins B6.7 240} EPA 2021, 240HP @ 2400 RPM, 560 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max), School Bus Only                                       |
| 12UYE                  | RADIATOR Aluminum, 2-Row, Cross Flow, Over Under System, 717 Sqln Louvered, with 313 Sqln Charge Air Cooler, Includes In-Tank Oil Cooler   |
|                        | Includes : DEAERATION SYSTEM with Surge Tank : HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber                        |
| 12TSY                  | FAN DRIVE (Borg-Warner SA85) Viscous Type, Screw On  |
|                        | <u>Includes</u><br>: FAN Nylon   |
| 12VBR                  | AIR CLEANER with Service Protection Element  |
|                        | Includes : GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted  |
| 12703                  | ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection   |
| 12VVN                  | CRUISE CONTROL Electronic  |
|                        | Notes : Cruise Control Switches Mounted on Steering Wheel are Non-Illuminated.   |
| 12WZE                  | EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations  |
| 12VHP                  | FEDERAL EMISSIONS (Cummins B6.7) EPA, OBD and GHG Certified for Calendar Year 2021   |
| 12VWH                  | GOVERNOR Electronic Road Speed Type; for Electronic Engines and Bus Models; with 55 MPH Default  |
| 12VYV                  | IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package  |
| 12UGN                  | THROTTLE, HAND CONTROL Electronic  |
|                        | Notes : Cruise Control Switches Mounted on Steering Wheel are Non-Illuminated.   |
| TRANSMISSION           |  |
| 13ARV                  | TRANSMISSION, AUTOMATIC {Allison 2500 PTS} 5th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus |
|                        | Includes : OIL FILTER, TRANSMISSION Mounted on Transmission  |

3

**Code Description** 

: TRANSMISSION OIL PAN Magnet in Oil Pan

13WYY SHIFT CONTROL PARAMETERS (Allison) 1000 or 2000 Series Transmissions, Performance Programming

TRANSMISSION OIL Synthetic; 20 thru 28 Pints 13WLN

**CLUTCH** 

11001 CLUTCH Omit Item (Clutch & Control)

#### **REAR AXLES, SUSPENSIONS**

AXLE, REAR, SINGLE {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends. Gear 14AKC

Ratio: 6.14

**14TBS** SUSPENSION, REAR, AIR, SINGLE (International IROS) 21,000-lb Capacity, 9.25" Ride Height, with Shock

Absorbers

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension;

Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

#### FRONT AXLES

2ASH AXLE, FRONT NON-DRIVING {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity

: AXLE, FRONT SQUARING to Plus or Minus .015 Inch, using a Special Fixture to Assure Parallelism of Springs

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension;

Brake System; Brakes, Front Air Cam; Wheels; Tires.

#### FRONT SUSPENSIONS

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock 3ADB

Absorbers

Includes

: SPRING PINS Bolt and Nut Type

: SPRING PINS Rubber Bushings, Maintenance-Free

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension;

Brake System; Brakes, Front Air Cam; Wheels; Tires.

#### CABS, COWLS, BODIES

16010 **COWL Flat Back** 

16HBA GAUGE CLUSTER English with English Electronic Speedometer

<u>Includes</u>

: GAUGE CLUSTER (5) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic),

Tachometer (Electronic), Voltmeter

: ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout

4

: WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage

(Visual and Audible)

16HLJ GAUGE, DEF FLUID LEVEL

GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission 16HGH

| <u>Code</u><br>16HKT | <u>Description</u> IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster  |
|----------------------|---|
| FRAMES               |   |
| 1CAC                 | FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 480.1" (12195mm) Maximum OAL  |
|                      | Includes : CHASSIS PAINT Chassis Painted Prior to Body Mounting : FRAME RAILS All holes Laser Aligned and Machine Punched, Powder Coated Prior to Full Assembly, Assembled in Fixture using "Grade 8" Bolts : FRAME REINFORCEMENT, SPECIAL 3.30" x 1.80" x 0.312" x 31.50" Inverted "L" in Front Shock Absorber Mounting Area   |
| 1LTV                 | BUMPER, FRONT Contoured, Steel, Heavy Duty  |
| 1LNT                 | CROSSING GATE, FRONT Omit Item  |
|                      | <u>Includes</u> : CROSSING GATE, FRONT Matches Contour of Bumper  |
| 1SAM                 | CROSSMEMBER, REAR, AF (2)   |
| 1WJE                 | WHEELBASE RANGE 276" (700cm) Only   |
| BRAKES               |   |
| 4091                 | BRAKE SYSTEM, AIR Dual System for Straight Truck Applications   |
|                      | Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6 |
|                      | Notes : Rear Axle is Limited to 19,000-LB GAWR with Code 04091 BRAKE SYSTEM, AIR and Code 04NDC BRAKES, REAR, AIR CAM Regardless of Axle/Suspension Ordered : Rear Axle is Limited to 20,000-LB GAWR with Code 04092 BRAKE SYSTEM, AIR and Code 04NCW BRAKES, REAR, AIR CAM Regardless of Axle/Suspension Ordered   |
| 4AZS                 | AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control   |
| 4XDD                 | BRAKES, FRONT {Meritor 15X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 5", 13,200-lb Capacity   |
| 4EXP                 | BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqln   |
| 4LAG                 | SLACK ADJUSTERS, FRONT {Gunite} Automatic   |
| 4XDR                 | BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle   |
| 4EXU                 | BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake   |
| 4SPA                 | AIR COMPRESSOR {Cummins} 18.7 CFM   |
| 4EBS                 | AIR DRYER {Bendix AD-9} with Heater   |

<u>Code</u> <u>Description</u>

4VCY AIR TANK LOCATION (1) Mounted Left Side to Provide Clearance for Larger Body Builder Supplied Battery

Box

4722 DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank

4WZT GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121

Requirements, for Conventional Bus

4LGG SLACK ADJUSTERS, REAR (Gunite) Automatic

**STEERING** 

5PSA STEERING GEAR (Sheppard M100) Power

5708 STEERING COLUMN Tilting

5CAL STEERING WHEEL 2-Spoke, 18" Dia., Black

**DRIVELINES** 

6DGA DRIVELINE SYSTEM (Dana Spicer) SPL100, for 4x2/6x2

**EXHAUST SYSTEMS** 

7BMK EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long

Horizontal Tail Pipe

7SCP ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

7WBL TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper

#### **ELECTRICAL SYSTEMS**

8000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: TURN SIGNAL FLASHER

: TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature

: TURN SIGNALS, FRONT Includes Reflectors; Flush Mounted

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with

Turn Signal Lever

: WIRING, CHASSIS Color Coded and Continuously Numbered

8GXK ALTERNATOR {Leece-Neville BLP4006HN} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote

Sense

8TTK BATTERY BOX Steel, with Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted

Left Side Behind Front Axle Perpendicular to Frame Rail

8MSG BATTERY SYSTEM (Fleetrite) Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

8XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

<u>Code</u> <u>Description</u>

8TPU COLLISION MITIGATION SYSTEM {Bendix Wingman Fusion} Adaptive Cruise Control w/Collision Mitigation

& Stationary Vehicle Braking, Stationary Object Alert, Lane Departure Warning, Overspeed Alert & Action; Includes Front Radar & Camera, Driver Display, Lane Departure Warning Switch & Speakers; Safety Direct

Capability, less Safety Direct Cable

8WXB HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

8WPB HEADLIGHTS Halogen, Composite Aero Design, with Daytime Running Lights

8WZL HEADLIGHTS, WIG WAG with Bus Pupil Warning Lights

8VAZ HORN, ELECTRIC (2) Trumpet Style, Mounted on Top of Mega-Bracket

8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

8XKL STARTING MOTOR (Mitsubishi Electric Automotive America 90P47) 12-Volt, with Soft-Start

8VZK TURN SIGNALS, FRONT Dual Face, LED, Amber/Red, Mounted on Top of Fender, Used with Standard Flush

Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors

**FRONT END** 

9WAY FRONT END Tilting, Fiberglass, with Three Piece Construction

Includes

: AIR INTAKE SYSTEM Integrated Pre-Cleaning System to Enhance Air Filter Life

: GRILLE Removable; Fiberglass Painted Hood Color : SPLASH SHIELD Integral with Front End Assembly

9HCW GRILLE Molded in Black

9WAB HOOD TILT ASSIST {EASY TILT} Mechanical

9AAE LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

10020 CHASSIS PAINT Full Chassis

10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100

**Includes** 

: PAINT SCHEMATIC ID LETTERS "NB"

10788 PAINT TYPE Urethane, One or Two Colors, Other than Imron or International.

10XAK PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500

Series Transmission on School and Commercial Buses (Supplied directly through Allison)

10DAS PROMOTIONAL PKG, CORR RESIST Corrosion Resistant Bus

10XAH PROMOTIONAL PACKAGE LED INTR {Sound Off/OptiLuxx} LED Lights

10XAJ PROMOTIONAL PACKAGE LED EXT {Sound Off/OptiLuxx} LED Lights

**FUEL TANKS** 

15SJT FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, with Low Profile

Fuel Filler Assembly and Vent Hosing, Mounted Between Frame Rails and Behind Rear Axle

15WEP DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow

WHEELS, TIRES - FRONT

<u>Code</u> <u>Description</u>

27DUW WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7482133285 (2) TIRE, FRONT 11R22.5 Load Range H X MULTI ENERGY Z (MICHELIN), 501 rev/mile, 75 MPH, All-

Position

#### WHEELS, TIRES - REAR

28DUW WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7482133285 (4) TIRE, REAR 11R22.5 Load Range H X MULTI ENERGY Z (MICHELIN), 501 rev/mile, 75 MPH, All-Position

#### WHEELS MISC OPTIONS

29580 WHEEL SEALS, FRONT (International) Oil-Lubricated Wheel Bearings

**BODY FEATURES** 

47BAK BUMPER, REAR Painted, 12" High, 3/16" Thick

47BAR SUPPORTS, REAR BUMPER Bolted to Frame

47AYB BODY, REAR Includes Emergency Door

**Includes** 

: DOOR, REAR EMERGENCY with Concealed Hinges

: HEADER BUMPER Padded, Mounted Over Rear Door; Upholstered to Match Passenger Seat Color

47ARH BOWS, ROOF 14 ga., One Piece Construction

Includes

: BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail

47BLU FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Fenders, Body

Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arm

47DXG FASTENERS, HANDRAIL Plusnuts & Screws

47APX FASTENERS, HEADLINER Screws

47AZL FLOOR, BODY with Wheel Wells

47PCA HANDLE, ASSIST Windshield Side Mounted, Left and Right, Stainless Steel, 4 Point Mount

47APR HEADLINER, BODY Conventional; 25'11"-34'11" Body Length, Perforated Full Length with Sound Insulation

Full Length

47ARP LIGHT BARS Plastic

47BBH LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated

47AXT RUB RAILS, BODY (4) Conventional; Steel, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", Body Length, Includes

Snow Rail

Includes

: RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices

47BBZ SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor

47AZE SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", Body

Length

47ASG SKIRT, BODY for Conventional, 14 1/2", 16ga

| <u>Code</u> | <u>Description</u> <u>Includes</u> : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets  |  |
|-------------|---|--|
| 47BLD       | STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish   |  |
| 47AUR       | TIE DOWNS, BODY Grade 8 Bolts, Every Body Section   |  |
|             | Includes : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning  |  |
| 47DAJ       | COVER, REAR DOOR INSIDE HANDLE Partial Coverage   |  |
| 47DNB       | DOOR, ENTRANCE, FRONT Electric, Outward Opening, with Split Pane Glass  |  |
|             | Includes : DOOR, ENTRANCE, FRONT Aluminum Frame with Pin Style Hinges, Ball Bearing Assisted, Interchangeable Top and Bottom Glass Lock : LOCK, ENTRANCE DOOR With Key Switch |  |
| 47DAK       | FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body  |  |
| 47DDE       | HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance  |  |
| 47DEY       | HANDLE, EXTERIOR, REAR Emergency Door; Yellow   |  |
| 47DDH       | HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover  |  |
| 47ALP       | INTERLOCK, STARTER with Key Switch, Electric Entrance Door with Locks, Outward Opening  |  |
| 47DDU       | LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke  |  |
| 47EWS       | LOCK, ENTRANCE DOOR, Electric Close Only with Toggle Switch   |  |
| 47DEK       | LOCK, REAR DOOR with Ignition Starter Interlock   |  |
| 47DRW       | RELEASE, ENTRANCE DR EXTERIOR Manual Door Control Right Front Electric Entrance Door  |  |
| 47EVY       | COMPARTMENT, LUGGAGE, LT MID 114" x 24" x 22"   |  |
|             | Includes : HINGES Rubber : LATCH, T-HANDLE, LOCKING Stainless Steel   |  |
| 47EWA       | COMPARTMENT, LUGGAGE, RT MID 114" X 24" X 22"   |  |
| 47EYB       | COMPARTMENT, TOOLBOX, LT FWD 13" x 15" x 25.5", with Lock   |  |
| 47EYE       | COMPARTMENT, TOOLBOX, RT AFT 13" x 15" x 25.5", with Lock   |  |
| 47EBM       | HOLD DOWN, BATTERY For (2) Standard Size Batteries  |  |
| 47LAU       | INSULATION, ROOF AND SIDES 1.50", All Models  |  |
| 47LAT       | NOISE REDUCTION, ROOF BOW Conventional; Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", Body Lengths  |  |
| 47MBA       | UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec  |  |
|             | Includes : UNDERCOATING Performed Before and After Mounting on Chassis  |  |
| 47SPB       | ALPHA/NUMERIC DECAL GUIDE Quantity 021-30   |  |
| 47MNT       | ARROW, RR DOOR, INSIDE Decal; Red, .75" Stroke, Indicating Handle Direction   |  |
| 47MNV       | ARROW, RR DOOR, OUTSIDE Decal; Black .75" Stroke, Indicating Handle Direction   |  |
| 47AJA       | BODY CERTIFICATION TAG Metal  |  |

| <u>Code</u><br>47APJ | <u>Description</u> BODY RATING TAG Metal; for State of Texas, Includes Design Capacity and Seat Capacity   |  |
|----------------------|--|--|
| 47AJC                | BODY TAG, METAL Capacity to Include the Total Number of Passengers   |  |
| 47PLX                | LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door   |  |
| 47MJR                | LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside  |  |
| 47MVA                | LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield   |  |
| 47MRU                | LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside   |  |
| 47NHL                | LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside   |  |
| 47MAV                | LETTERS, SCHOOL BUS SIDE Decal; "SCHOOL BUS"; in 8" Reflective Black Letters, Each Side  |  |
| 47BKK                | LETTERS, SCHOOL BUS FRONT/REAR Decal; "SCHOOL BUS"; with 8" Black Reflective Letters, 3M Fluorescent Diamond Grade, Yellow On Front and Rear Cap |  |
| 47MVC                | LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser  |  |
| 47NTE                | LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door Over Driver Window and Entrance Door           |  |
| 47NMG                | OPERATING INSTR, REAR Decal, Inside Rear Emergency Door  |  |
| 47NJA                | PAINT COLOR, BODY EXTERIOR 4421 School Bus Yellow  |  |
| 47NKR                | PAINT COLOR, BODY INTERIOR Light Gray  |  |
| 47NJS                | PAINT COLOR, BUMPER Rear, 0001 Canyon Black  |  |
| 47NKD                | PAINT COLOR, ROOF 9219 Winter White, Beginning 5" Above Drip   |  |
| 47NAB                | PAINT COLOR, RUB RAILS 0001 Canyon Black   |  |
| 47NJM                | PAINT FLASHER BACKGRD 0001 Canyon Black  |  |
| 47NTY                | PAINT HOOD AND FENDER To Match Body Exterior   |  |
| 47NKL                | PAINT, RUB RAIL Flange to Flange   |  |
| 47NGJ                | PAINT, WINDOW BOW CAPS 0001 Canyon Black, Side Only  |  |
| 47NGW                | SEAL, RUB RAILS Top Edge, All Rails  |  |
| 47NXH                | STRIPING, E/E WINDOW, LEFT {3M} (02) Perimeter, 1" Yellow Fluorescent Diamond Grade  |  |
| 47NWU                | STRIPING, E/E WINDOW, RIGHT {3M} (02) Perimeter, 1" Yellow Fluorescent Diamond Grade   |  |
| 47NXN                | STRIPING, PERIMETER, REAR {3M} Emergency Door, 1" Yellow Fluorescent Diamond Grade   |  |
| 47NWR                | STRIPING, REAR END {3M} 2" Yellow Fluorescent Diamond Grade  |  |
| 47NWT                | STRIPING, ROOF HATCH, FRONT (3M) Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade   |  |
| 47NWH                | STRIPING, ROOF HATCH, REAR {3M} Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade  |  |
| 47NWJ                | STRIPING, SEATLINE {3M} 2" Yellow Fluorescent Diamond Grade  |  |
| 47MTY                | WIRING DIAGRAM Schematic, Electrical   |  |
|                      | Includes : ACCESS PANEL for Wiring Diagram Schematic Located on Body Exterior; Below Driver Window   |  |
| 47SBB                | SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", Body Length   |  |
| 47BDA                | FLOOR, COATING, Chemguard Metal Coating, Applied to Main Floor and Intermediate Sills  |  |

<u>Code</u> <u>Description</u>

47KDC MONITOR, POST TRIP INSPECTION (Leave No Student Behind) Accessory Controlled, with Push Button

Alarm Disable at Rear of Bus Prompts Driver to Walk to Back of Bus and Push Button in Light Bar to Deactivate

System

47DNN SWITCH, LOCATION Left of Driver; Includes Master Flasher, Amber Flasher, and 2 Position Door Control

**BODY FEATURES** 

48ANT WINDOW, DRIVER Laminated, Clear

48ANM WINDOW, ENTRANCE DOOR, BOTTOM Laminated, Clear

48ANE WINDOW, ENTRANCE DOOR, TOP Laminated, Clear

48BJL COLOR, WINDOW FRAME, PASS (26) Passenger Window, Black

48BAH WINDOW, E/E, LEFT (2) Vertical Hinge

48BKP WINDOW, E/E, RIGHT (2) Vertical Hinge

48AUN WINDOW, PASSENGER, TINT Conventional; 28% Light, Laminated Glass, 78" Headroom, with 31'2", 31'11",

32'8", 33'5", 34'2", 34'11" Body Length

48ARU WINDOW, SASH (20) 27" Sections, 9"x 23" Opening

48ASP WINDOW, SASH +9 SECTIONS (2) 9" x 32 1/4" Opening

48APL WINDOW, STOPS 12" Opening, Only with 78" Headroom

48PAM WINDSHIELD 3 Flat Pieces, 73% Light, with Band

48PAY AISLE POSITION Center, for balanced seating

48PBB FLOOR COVERING, COLOR Black

48PUP FLOOR COVERING, TRIM Omit

48UWV FLOOR COVERING, TYPE Koroseal, One Piece, Vinyl, All Body Lengths, Black

48VVR STEP TREADS (Koroseal) Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded

Steps

48PAV WHEEL POCKET COVER Plastic, ABS

48PKC HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System

48PKR FAN, DEFOG LEFT CENTER 6.50" Diameter, Black, Mounted Left of Center Post, 2-Speed Switch in Panel

48PPM HEATER CUT OFF, VALVE Ball, with Butterfly Handle

48PPP HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Driver Area

48GYV HEATER, DEFLECTOR Kit, for Driver Heater

48GHC HEATER, DRIVER 90,000 BTU, with Defroster and without Rear Heat Duct

Includes : AIR FILTER

: HEATER HOSES Premium

: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

48PMJ HEATER, PASS, LT REAR 84,500 BTU

Includes : AIR FILTER

48PNW HEATER, WATER PUMP (2 MPU 12) Self Priming, with Plastic Housing

<u>Code</u> <u>Description</u>

48PZP ROOF HATCH, FRONT {Specialty 9245-0200} Emergency Exit with Alarm
48PZR ROOF HATCH, REAR {Specialty 9245-0200} Emergency Exit with Alarm

48PPS ROOF VENT, FRONT Static

48PPC SWITCH, HTR FAN, REAR, LT with 84,500 BTU Rear Heater Only

48PTT ARM REST, DRIVER, RIGHT {National}
48NAT FITTINGS, AIR SEAT for Driver Seat

48VUK SEAT, DRIVER {National ABTS 2000} Air Suspension Dual Shock, High Back with Integral Headrest, Isolated,

with 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Adjustable Lumbar Support,

Includes Additional Padding, 3 Point Lap and Shoulder Belts

**Includes** 

: SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor

48PXP UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz.

48PVK UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Brown
48PVA UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert

48PWR UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz.
48RAE BARRIER, CRASH, AFT ENTRY DOOR 39", 1 Leg

48RAL BARRIER, CRASH, AFT DRIVER 39", 1 Leg

48RGR HAND RAIL, ENTRANCE DOOR, AFT Stainless Steel, 4", Above Step

48RGE HAND RAIL, ENTRANCE DOOR, FWD Stainless Steel; Curved

48ACN SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing

48USV SEAT BACK, PASSENGER High Back

48XGC SEAT,PASS,3PT,LT,26",2 LEG {BTI Seating System} (01) High Back, with 3 Point Seat Belts
48YAH SEAT,PASS,3PT,LT,39",2 LEG {BTI Seating System} (12) High Back, with 3 Point Seat Belts
48YAX SEAT,PASS,3PT,RT,39",2 LEG {BTI Seating System} (13) High Back, with 3 Point Seat Belts

48PWA UPHOLSTERY, PASS SEATS, COLOR Brown, for Seats, Barriers and Head Bumpers

48PHR UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (25-26) Seats

48RLX CUSHION, SEAT 15" Depth

<u>Includes</u>

: WARRANTY Four Years

48RRA UPHOLSTERY, SEAT, STITCHING Single

<u>Includes</u>

: WARRANTY Two Years

**BODY FEATURES** 

49MZT INSULATION, FUEL FILLER Rubber Isolator for Fuel Filler when Exhaust are on Same Side

49AMJ ALARM, BACKING {Ecco #575} 107 db

49AMT CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses

<u>Includes</u>

| <u>Code</u> | <u>Description</u> : ACCESS PANEL for Body and Chassis Fuses/Circuit Breakers Located on Body Exterior; Below Driver Window  |
|-------------|--|
| 49AJH       | CONNECTION, LIGHTS Cluster, Clearance and Side Marker To Tail Lights   |
| 49BCN       | FLASHER SYSTEM (8) Warning Lights, 8-Lamp System, Electronic Relay Flasher, Non-Sequential Operation, Red Lights Activate with Door Open   |
| 49DBR       | HOOD, WARNING LAMP (4) Black, 8-Lamp System, One Hood Above Two Lights   |
| 49JBU       | LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light  |
| 49BCR       | LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection  |
| 49DAG       | LIGHT, INDIC, WARNING LIGHTS LED Type; Red and Amber   |
| 49JBV       | LIGHT, LICENSE PLATE {Sound Off/OptiLuxx} LED, with Mounting Gasket  |
| 49JBW       | LIGHT, STEP {Sound Off/OptiLuxx} 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door   |
| 49EYH       | LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High  |
| 49AHV       | LIGHT, STROBE, STOP SIGN, FRT In Lieu Of Flashing Lights Furnished with Stop Sign, Speciality  |
| 49AHY       | LIGHT, STROBE, STOP SIGN, REAR In Lieu of the two Flashing Lights Furnished with Stop Sign, Speciality   |
| 49ZNC       | LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange   |
| 49NGD       | LIGHTS, BACK UP, ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Oval LED Mounted on Left and Right Skirts, Aft of Rear Wheel Pocket Area, Below Seat Line Rub Rail, Illumination at Rear Tire, Wired to Reverse Light Signal |
| 49JBS       | LIGHTS, CLUSTER (Sound Off/OptiLuxx) Oval, 4 Internal LEDs per Light; Amber Front and Red Rear   |
| 49BYY       | LIGHTS, DIRECTIONAL, FRONT {Sound Off/OptiLuxx} with Park, 7" Round Amber LED, on Front Cowl   |
| 49BYZ       | LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber   |
| 49EAX       | LIGHTS, DIRECTIONAL, SIDE (4) {Sound Off/OptiLuxx} Rectangular LED Armored, 2 Each Side First Section Aft Entrance Door & Forward Rear Wheel Pocket  |
| 49JBP       | LIGHTS, DOME (Sound Off/OptiLuxx) (07) LED, Rectangular Recessed Type, Mounted in Light Bar  |
| 49ESC       | LIGHTS, DOME, DRIVER {Sound Off/OptiLuxx} (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch  |
| 49BYV       | LIGHTS, MARKER, FRONT & REAR (8) {Sound Off/OptiLuxx} LED, Rectangular, Armored, (4) Amber Front and (4) Red Rear  |
| 49EAW       | LIGHTS, MARKER, SIDE, INTERMED (Sound Off/OptiLuxx) LED, Amber, Rectangular, Armored, Intermediate, Centered, Required for Units 30 Foot or Longer   |
| 49BYT       | LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red  |
| 49ZNG       | LIGHTS, STOP & TAIL ADDITIONAL (2) (Sound Off/OptiLuxx) 4" Round LED, Red, with Flange   |
| 49NGJ       | LIGHTS, WARNING (8) {Sound Off/OptiLuxx} (4) 7" Round Red Strobing LED and (4) 7" Round Amber Strobing LED, 2 Front, 2 Rear Each Color   |
| 49BDL       | MONITOR, LIGHT SYSTEM (Sound Off/OptiLuxx) with 16 LED or Incandescent Indicator Lights  |
| 49BZU       | RADIO, ENTERTAINMENT (Custom Radio) AM/FM Stereo/USB Input, Includes Antenna and Cable, with Public Address System   |
| 49ANU       | SOURCE, POWER 12 VDC, Mounted In Dash  |
| 49AWU       | SPEAKERS AND WIRING (6) Flush Mounted in Light Bar   |
|             |  |

| <u>Code</u><br>49ELC | <u>Description</u> STOP ARM, FRONT Electric, Composite Blade, 18" Octagon, Double Sided, 1/2" White Border, Hi Intensity Grade, Strobing LED Lights |
|----------------------|---|
| 49ELG                | STOP ARM, LEFT REAR Electric, Composite Blade, 18" Octagon, Single Sided, 1/2" White Border, Hi Intensity Grade, Strobing LED Lights                |
| 49AMD                | SWITCH, DRIVER PANEL, TYPE Rocker   |
| 49SAA                | SWITCH, INSTRUMENT PANEL LIGHTS; Rheostat   |
| 49ANH                | SWITCH, MAGNETIC, DISCONNECT Master, Ignition Operated, All Body Circuits   |
| 49EVL                | SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP ", for Separate Solenoid, with Red Switch in Panel                                    |
| 49AMY                | SWITCH, REAR DOOR BUZZER for Emergency Door   |
| 49BLL                | WIRING, VIDEO SYSTEM Power and Ground Connection Only; Connection in Flasher Plate Area with 20 Amp Fuse Protection                                 |
| 49HJX                | MIRROR, BRACE, EXTERIOR Telescoping for Stainless Steel Breakaway Bracket   |
| 49BVH                | MIRROR, CROSS VIEW, EXTERIOR (2) {Mirror Lite High Definition Busboy} Stainless Steel   |
| 49EGB                | MIRROR, INSIDE 10" x 30", Clear   |
| 49EJS                | MIRROR, REAR VIEW, EXTERIOR {Rosco} Stainless Steel, Motorized Head, Heated, Breakaway Bracket, Suspended   |
| 49ENK                | VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield  |
| 49GDS                | COMPARTMENT ABOVE DRIVER Left of the Driver   |
|                      | Includes<br>: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10"<br>: HINGES Piano Type   |
| 49GGE                | FIRE EXTINGUISHER, DRIVER AREA 5 lb 2A-40BC Minimum with Flexible Hose and Metal Nozzle   |
| 49GAY                | KIT, BODY FLUID Texas   |
| 49EBA                | KIT, FIRST AID Plastic; 24 Unit, Spec State   |
| 49MZV                | LATCH, COMPARTMENT Locking, for Overhead Storage Compartment  |
| 49GDG                | PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light   |
| 49GLP                | REFLECTORS, REAR (2) 3", Red, Mounted with Screws   |
| 49GLM                | REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted with Screws                                    |
| 49GLA                | REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third Rub Rail From the Top                                |
| 49GLG                | REFLECTORS, SIDE, REAR (2) 3", Red, Mounted with Screws   |
| 49GEP                | SAFETY TRIANGLES Warning Reflectors, Ship Loose   |
| 49GUB                | CUTTER, SEAT BELT {TIE TECH Safecut} for Cutting Seat Belts   |
| 49GCC                | CUTTER, SEAT BELT, LOCATION Centered on Inside of Driver Compartment Lid  |
| 49JAC                | DEF FILLER DOOR with Non-Locking Latch  |
| 49GUK                | FENDERS, RUBBER, REAR (2)   |
| 49MZS                | FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position   |

<u>Code</u> <u>Description</u>

49CKS FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Left Side Fill for Between the Rail

Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only

49GUM INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel

49GVA MUD FLAPS, FRONT WHEELS (2) Anti-Sail and Anti-Spray

49GUY MUD FLAPS, REAR WHEELS (2) Anti-Spray, Anti-Sail

49GWW WINDSHIELD WASHER Kit; 6 Quart Capacity, Bottle

<u>Includes</u>

: WINDSHIELD WASHER ELECTRICAL CONNECTIONS Sealed and Locking Type

49GBV WINDSHIELD WIPERS (2) Cowl Mounted

<u>Includes</u>

: WINDSHIELD WIPERS CONTROL Single Motor, Overlapping Wipe Pattern

49UBZ STATE OF OPERATION Texas

Services Section:

WARRANTY

40126 WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later,

CTS-3304H

40RAP SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for

Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage

& ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident

40PLG SRV CONTRACT, EXT VEH COVERAGE {Navistar} To 60-Month/100,000 Miles (160,000 km), Covers 100%

Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or

Corrosion of Cab/Cowl Structure and Paint

**BODY FEATURES** 

49GVN WARRANTY 5-Year, Limited

DOT INSPECTION - Set Govern speed @ 65mph

PRE DELIVERY INSPECTION - Pro Air

WEIGHT SLIP

3PT SEAT INCENTIVE

Defrost Kit, Pro Air

Bus Air 136K BTU Air Conditioning PRO AIR

6 Camera Safety Vision installed LHB, #E180005958

ROSCO SAFE-T-SCOPE 360 CAMERA SYSTEM WITH 7" MOR-VISION ULTRA BRIGHT MONITOR IN 10"X30" MIRROR. 4 CAMERAS: FRONT, REAR, TWO SIDES. INSTALLED AT IC PLANT TULSA.

ADDITIONAL SPA INVOICE CREDIT

#### December 01, 2020

**Price** 

# Financial Summary 2022 INTEGRATED CE S BUS (PB105)

(US DOLLAR)

**Description** 

| Net Sales Price:  | \$469,176.00  |
|---|---|
| Please feel free to contact me regarding these specifications pleased with the quality and service of an IC Corporation veh | should your interests or needs change. I am confident you will be<br>nicle.   |
| PRICE PER VEHICLE: \$117,294.00   |   |
| FOUR (4) VEHICLES: \$469,176.00   |   |
| BUY BOARD FEE: \$800.00<br>PRICE DOES NOT INCLUDE BUY BOARD FEE \$800 PER PI<br>CONTRACT #630-20                            | URCHASE ORDER, PLEASE ADD IF APPLICABLE. BUY BOARD  |
| Approved by Seller:   | Accepted by Purchasers  |
| Official Title and Date   | Firm or Business Name   |
| Authorized Signature  | Authorized Signature and Date   |
| This proposal is not binding upon the seller without Seller's Authorized Signature  |   |
|   | Official Title and Date   |
| The TOPS FET calculation is an estimate for reference purand reporting/paying appropriate FET to the IRS.                   | rposes only. The seller or retailer is responsible for calculating  |
|   | ed herein are Navistar, Inc.'s standard printed warranties which ave been provided a copy and hereby agree to their terms and |