



TURNKEY Network Solutions

7020 Southbelt Drive SE Caledonia, MI 49316
Toll Free: 877.376.7681 www.tkns.net

The Single Source for
All Your Telecommunications
Infrastructure Needs

To: Kent Intermediate School District	Contact: Glen Finkel
Address: 2930 Knapp NE Grand Rapids, MI 49525 USA	Phone: (616) 364-1333 Fax: (616) 364-1489
Project Name: Kent ISD NJUNS Review	Bid Number: 2024-1287
Project Location: Grand Rapids, MI	Bid Date: 8/6/2024

Scope of Work: Quote includes time and materials to investigate and repair (if needed) 142 existing NJUNS Tickets. The detailed list of NJUNS tickets is attached.
TKNS to invoice actuals upon completion of the project

Thank you for the opportunity to quote this project.

Item Description	Estimated Quantity	Unit	Unit Price	Total Price
Aerial Maintenance - Scheduled	580.00	HR	\$110.00	\$63,800.00
OSP Materials	1.00	LS	\$6,565.66	\$6,565.66
			Total Bid Price:	<u>\$70,365.66</u>

Notes:

- This quote constitutes an offer by TurnKey Network Solutions (TKNS) to the Customer named on page 1 of this quote for the furnishing of Products and/or Services. The offer made in this quote is subject to the Master Services Terms and Conditions available at <http://www.tkns.net/wp-content/uploads/2021/03/TKNSMSTC.pdf> Customer shall indicate acceptance of this offer by providing TKNS with a return copy of the quote signed by a duly authorized representative of Customer. By accepting this offer Customer accepts TKNS Master Services Terms and Conditions.
- Labor prices are valid for sixty (60) days from the date noted on the quote. Beyond sixty (60) days, please call for current pricing.
- Materials prices are subject to change without prior notice due to supply chain related pricing volatility from suppliers. The final cost of the materials shall be equitably adjusted, should they be greater than the amount proposed within the accepted quote.**
- All routes will be owned by and permitted under Customer of record listed on quote.
- Customer of record listed on quote is responsible for all structure (pole and conduit) make-ready costs, applicable structure (pole and conduit) permits, fees, and ROW acquisition/use fees.
- Price does not include any costs for directional boring/plowing through rock or frozen ground (frost) conditions. A price will be agreed upon prior to construction if these conditions are encountered.
- All property disturbed by TKNS will be restored to its original condition.
- Quoted price does not include the cost to modify any TKNS disturbed area to meet The Americans with Disabilities Act (ADA). Any requirement of modifications to disturbed areas outside of restoral to its original condition will be considered a change in the scope of work and a price will be agreed to prior construction.
- Excavated spoils shall be used as backfill. Any requirement for imported backfill will be considered a change in the scope of work and a price will be agreed upon prior to construction.
- TKNS is not responsible for the handling and disposal of Hazardous materials.
- The information contained in this quotation (the "Proprietary Information"), is proprietary to the business of TKNS. Customer agrees to protect as confidential all Proprietary Information provided by TKNS. This provision shall survive the termination of any contractual relationship between TKNS and Customer. Customer shall protect and treat Proprietary Information as it does its own most confidential proprietary information, and shall not share it with any outside person whatsoever. For the avoidance of doubt, the fact and contents of any discussions and the contents and existence of this quotation shall be considered Proprietary Information.
- Fax purchase orders to: 616.825.6131 or email purchaseorders@tkns.net.
- This quote may or may not include estimated taxes. If taxes are included, the amount reflected is an estimate and the actual amount will be billed at the time of invoice. By accepting this quote Customer agrees to pay in addition to this quote any taxes as required.**

Payment Terms:

Payment in full is due within thirty (30) days of receipt of invoice. Unpaid balances shall bear interest from the due date at the rate of one and one

half percent (1 1/2 %) per month.

ACCEPTED:

The above prices, specifications and conditions are satisfactory and are hereby accepted.

Buyer: _____

Signature: _____

Date of Acceptance: _____

CONFIRMED:

TurnKey Network Solutions

Authorized Signature: _____

Estimator: Jennifer Grams

616-988-8727 jgrams@tkns.net

Entered Date	Due Date	Owner ID	Ticket #	Address of Work	County	City	Description of Work	Pole Number
7/14/2024	10/5/19	CEGRN	VIO4021862	3965 W RIVER DR NE	Kent	Plainfield	Kent ISD to lower a minimum of 12" to make room for Comstock Park Public School to lower. Maintain 12" separation with Comstock Park Public School at pole, 6" separation with comms in midspans, and 15'6" ground clearance in NE span. Kent ISD to install a down guy marker	CE ID# 0526046
7/14/2024	4/23/20	CEGRE	VIO3827179	5991Crestmoor Dr	Kent	Grand Rapids	KISD TO LOWER A MINIMUM 4'2" TO CORRECT 6" MIDSPAN SEPARATION VIOLATION IN THE EAST SPAN. MAINTAIN A MINIMUM 12" OF SEPARATION ABOVE COMCAST BOX AND A MINIMUM 15'6" GROUND CLEARANCE IN BOTH SPANS.	0080376
7/14/2024	4/24/20	CEGRW	VIO3606514	3515 PRARIE ST SW	Kent	Grandville	KISD to lower a minimum of 12" in order to allow room for comms to lower. Maintain a minimum 15'6" ground clearance	CE ID# 0473444
7/14/2024	4/26/20	CEGRE	VIO4230321	1889 60th St SE	Kent	Grand Rapids	KISD TO LOWER A MINIMUM 1'4" TO CORRECT 12" SEPARATION VIOLATION WITH STEELCASE AND TO MAKE ROOM FOR MCI METRO TO ATTACH ABOVE. MAINTAIN A MINIMUM 15'6" GROUND CLEARANCE.	CE ID # 0984124
7/14/2024	4/26/20	CEGRW	VIO4231045	NE Corner Prairie St	Kent	Grandville	KISD to lower a minimum of 6" in order to allow room for 123NET to lower. Maintain a minimum 15'6" ground clearance. NEW WORK 1/17 /2024 KISD TO LOWER AT LEAST 6" TO CORRECT ATTACHMENT AND MIDSPAN SEPARATION VIOLATIONS. MAINTAIN AT LEAST 12" ATTACHMENT, 6" MIDSPAN SEPARATIONS BELOW 123NET AND 15'6" MIDSPAN GROUND CLEARANCE.	0320413
7/14/2024	5/1/20	CEGRW	VIO4238110	1633 E Beltline Ave NE	Kent	Grand Rapids	Kent ISD to lower a minimum of 6" to allow 123Net to lower. Maintain a minimum 12" attachment separation above power supply box, and maintain a minimum 15'6" ground clearance. NOTE: Kent ISD to raise at adjacent pole to the north.	CE ID# 0643026
7/14/2024	5/1/20	CEGRW	VIO4238116	1633 E Beltline Ave NE	Kent	Grand Rapids	Kent ISD to raise a minimum of 2'7" to correct the 15'6" ground clearance violation in the south span. Maintain a minimum 12" attachment separation and 6" midspan separation below 123Net. NOTE: Kent ISD to lower at adjacent pole to the south.	CE ID# 0035590
7/14/2024	5/1/20	CEGRW	VIO4238120	1633 E Beltline Ave NE	Kent	Grand Rapids	Kent ISD to lower a minimum of 4" to correct the 12" attachment separation violation with 123Net. Maintain a minimum 15'6" ground clearance.	CE ID# 1286217
7/14/2024	5/17/20	CEGRE	VIO3782741	1823 60TH ST SE	Kent	Grand Rapids	KISD to lower main line attachment a minimum of 12" to correct 6" mid span separation violation and to make room for MCI metro to attach. Maintain 15'6" mid span ground clearance	CE ID# 0151549
7/14/2024	5/17/20	CEGRE	VIO3946361	1773 60TH ST SE	Kent	Grand Rapids	KISD to lower main line attachment a minimum of 4" to allow other comms to lower out of violation. Maintain 15'6" ground clearance. (See adjacent pole to the east for more corrections)	CE ID# 0151551
7/14/2024	6/10/20	CEGRE	VIO4282006	EASTERN AVE SE	Kent	Kentwood	KISD lower attachment at least 6" to obtain 12" separation from streetlight drip loop. Maintain 15'6" minimum ground clearance.	CE ID# 0834559
7/14/2024	6/12/20	CEGRW	VIO3091771	2929 Burlingame Ave	Kent	Wyoming	KISD TO PROPERLY SECURE CABLE TO POLE	CE ID# 0536132
7/14/2024	7/15/20	CEGRW	VIO3716214	146 32ND ST SE	Kent	Wyoming	KISD TO LOWER A MINIMUM 2'7" TO CORRECT 12" SEPARATION VIOLATION WITH US SIGNAL AND COMCAST AND 6" MIDSPAN SEPARATION VIOLATION IN THE WEST SPAN WITH COMCAST AND AT&T. MAINTAIN A MINIMUM 15'6" GROUND CLEARANCE IN BOTH SPANS. COORDINATE WITH AT&T TO BE ON SITE TO LOWER. CONTACT INFO: DANNY GARRETT, PHONE: 734-266-6445 EMAIL: dg1716@att.com	0834370
7/14/2024	7/16/20	CEGRW	VIO3769961	3221 Division Ave S	Kent	Grand Rapids	: KISD TO LOWER A MINIMUM 6" TO ALLOW ITP TO LOWER. MAINTAIN A MINIMUM 15'6" GROUND CLEARANCE IN BOTH SPANS.	CE ID # 0112239
7/14/2024	7/30/20	CEGRW	VIO3770100	3355 Division Ave S	Kent	Grand Rapids	KISD to lower a minimum of 1'4" to allow room for ITP to lower. Maintain a minimum of 15'6" midspan ground clearance. Decrease guy lead to 5' to allow room for AT&T to fix anchor violation.	CE ID # 0816218
7/14/2024	8/12/20	CEGRE	VIO4352510	1689 60TH ST SE	Kent	Kentwood	: KISD to lower attachment a minimum of 1'4" to correct 6" midspan separation violation in East span and tom make room for MCI metro to attach. Maintain minimum 15'6" midspan ground clearance	CE ID# 0151554
7/14/2024	8/27/20	CEGRE	VIO3782697	5496 EASTERN AVE	Kent	Kentwood	KISD to raise a minimum of 1'2 to correct the 15'6" ground clearance violation maintaining 12" separation and 6" midspan separation violation below Comcast. Note : also raising at pole to the South.	0834693
7/14/2024	9/16/20	CEGRW	VIO3414159	3618 Burlingame Ave. SW	Kent	Wyoming	EXTEND DOWN GUY 8', GUY FAILS @ 147%	1173414
7/14/2024	9/17/20	CEGRW	VIO3742361	PLYMOUTH AVE NE	Kent	Grand Rapids	KISD to lower attachments in the East and South spans a minimum of 4" in order to correct a 12" attachment separation violation and 6" mid span separation violation in the North and South span. Maintain a minimum of 15'6" ground clearance.	CE ID# 0823110

7/14/2024	9/19/20	CEGRW	VIO4012841	NW Corner FULTON ST E	Kent	Grand Rapids	: KISD TO LOWER ATTACHMENT A MINIMUM OF 9" TO ALLOW MCLEODUSA TO LOWER ATTACHMENT. MAINTAIN 15'6" GROUND CLEARANCE.	0823134
7/14/2024	9/27/20	CEGRW	VIO4400518	1355 SHERMAN ST SE	Kent	Grand Rapids	: KISD to lower attachment a minimum of 5" in order to correct 12" attachment separation violation, maintain a minimum of 15'6" ground clearance.	1197333
7/14/2024	9/28/20	CEGRW	VIO4400587	1000 1008 BRETON RD SE	Kent	Grand Rapids	Kent Intermediate School District to lower the stranded attachment a minimum of 1'2" to correct the 6" comm midspan separation violation in the north span and to allow Everstream to lower. Maintain a minimum 15'6" ground clearance.	0039037
7/14/2024	10/2/20	CEGRN	VIO3482035	NW Corner WEST RIVER DR NE	Kent	Plainfield	KISD to lower stranded attachment a minimum of 12", reduce anchor lead a minimum of 6". Work being done to correct 6" midspan separation violations to E and W, allow AT&T room to install proper guying, correcting violations. Maintain minimum 15'6" midspan ground clearance(minimum 18' over all roads), minimum 5' anchor separation from pole.	0113406
7/14/2024	10/8/20	CEGRW	VIO4407386	PRAIRIE ST SW	Kent	Grandville	Kent ISD to lower a minimum of 5" to correct 12" attachment separation violation. Maintain 15'6" midspan ground clearance violation. NOTE: Kent ISD to raise on adjacent pole to west.	CE ID # 1343085
7/14/2024	10/14/20	CEGRW	PT3765776	129 32ND ST SW	Kent	Wyoming	After CE work, KISD lower attachment at least 24" to obtain 6" midspan separation below Century Link in east span, and to allow comms above to lower. Maintain 15'6" minimum ground clearance.	CE ID# 0816195
7/14/2024	10/23/20	CEGRW	VIO4385327	1587 36th St SW	Kent	Wyoming	: KISD to raise attachment 2'0" to correct a 12" attachment and 6" midspan separation violation with MCI Metro. Maintain 12" attachment and 6" midspan separation below Comcast.	0524034
7/14/2024	10/24/20	CEGRW	VIO4239170	3175 LEONARD ST NE	Kent	Grand Rapids	KISD to lower wire a minimum of 4" to allow for comms above to lower to fix violations. Maintain a 15'6" midspan ground clearance and install a downguy to support the east span. Install a minimum of a 8' lead west.	CE ID# 0008340
7/14/2024	1/14/21	CEGRW	PT4256435	Sherman St Se	Kent	Grand Rapids	Kent ISD to transfer to new pole 12" below Comcast due to Verizon installing an antenna system. Maintain minimum 6" midspan separation below Comcast and minimum 15'6" ground clearance. Install strain insulator on down guy.	1197334
7/14/2024	3/17/21	CEGRE	PT4494676	813 TIERRA AVE SE	Kent	Grand Rapids	: KISD TO LOWER ATTACHMENT A MINIMUM OF 6" TO ALLOW MCI METRO TO LOWER ATTACHMENT. MAINTAIN 15'6" GROUND CLEARANCE.	0834524
7/14/2024	3/20/21	CEGRW	VIO3757878	3699 PRAIRIE ST SW	Kent	Grandville	KISD lower a minimum of 4" to correct the 12" comm separation violation with 123.net. Maintain 15'6" ground clearance	0320409
7/14/2024	3/21/21	CEGRW	VIO4582991	2033 Lake Dr. SE	Kent	East Grand Rap	: Kent Intermediate School District: Lower attachment a minimum of 4" to allow AT&T to lower and correct 12" at pole separation violation. Maintain 15'6" ground clearance.	0039072
7/14/2024	3/28/21	CEGRW	VIO3765770	29 32ND ST SW	Kent	Grand Rapids	KISD lower attachment at least 16" to obtain 6" midspan separation form Century Link in east span. Maintain 15'6" minimum ground clearance.	CE ID# 0816188
7/14/2024	4/16/21	CEGRW	VIO4582921	1961 Lake Dr. SE	Kent	East Grand Rap	Kent Intermediate School District: Lower attachment a minimum of 8" to correct 12" at pole separation violation. Maintain 12" at pole separation and 6" midspan separation below E Grand Rapids Public Schools. Maintain 15'6" ground clearance.	0039081
7/14/2024	6/5/21	CEGRW	VIO4385339	1514 36th St SW	Kent	Wyoming	: KISD to lower attachment 4" to correct a 12" attachment separation violation with AT&T. Maintain 12" attachment and 6" midspan separation above MCI Metro	0524037
7/14/2024	6/12/21	CEGRW	PT3682771	3557 PARKLAND AVE SW	Kent	Wyoming	KISD to lower 5" to correct a 12" attachment separation violation with AT&T. Maintain 12" attachment and 6" midspan separation above MCI.	0524040
7/14/2024	6/12/21	CEGRW	VIO4462924	1299 36TH ST SW	Kent	Wyoming	KISD to lower attachment 12" to correct a 12" attachment separation violation with AT&T and to allow above comms to lower out of violation. Maintain 12" attachment and 6" midspan separation above MCI Metro.	CE ID# 0539522
7/14/2024	8/25/21	CEGRW	PT4400594	621/625/620 Giddings Ave SE	Kent	Grand Rapids	: KISD to transfer to new pole at a minimum of 12" on pole separation below AT&T, maintain a minimum of 16'0" ground clearance across both spans. Note: MCI Metro to attach below	1197351
7/14/2024	1/29/22	CEGRW	VIO4231308	NE Corner Prairie St	Kent	Grandville	KISD raise a minimum of 12" to correct the 18'0" road clearance violation. Maintain 12" comm separation and 6" comm mid span separation with 123.net.	0429706
7/14/2024	2/18/22	CEGRW	VIO4659647	LEONARD ST NE	Kent	Grand Rapids	: KISD attach to pole. Maintain a 12" at pole separation and 6" midspan separation below US Signal. Maintain a 15'6" at pole ground clearance and midspan ground clearance	1284109

7/14/2024	2/25/22	CEGRN	PT4910249	675 6 Mile Rd NW	Kent	Alpine	KISD to transfer to new pole. Maintain a minimum of 12" attachment and 6" midspan separation below Comcast. Maintain a minimum of 18' midspan ground clearance in both spans	0660307
7/14/2024	2/27/22	CEGRN	VIO4981482	5267 Division Ave N	Kent	Alpine	Kent Intermediate School District Lower attachment a minimum of 7" to correct 12" at pole separation violation with Comstock Park Public Schools. Maintain minimum 15'6" midspan ground clearance in the W span and resag span E to maintain 18'0" midspan ground clearance over road.	0475265
7/14/2024	3/3/22	CEGRW	VIO4385384	1413 36th St SW	Kent	Wyoming	KISD to lower attachment 5" to correct a 12" attachment separation violation. Maintain 12" attachment and 6" midspan separation above MCI Metro.	0547352
7/14/2024	3/5/22	CEGRW	VIO3442970	1223 Aberdeen St	Kent	Grand Rapids	Kent ISD to lower a minimum of 8" to correct the 12" separation and the 6" midspan separation violation. Maintain a minimum 16'6" ground clearance.	CE ID# 0663103
7/14/2024	3/11/22	CEGRW	VIO3637915	2780 Leonard St NE	Kent	Grand Rapids	KISD lower attachment a minimum of 4" to correct the 12" midspan separation violation. Maintain a minimum 15'6" midspan ground clearance. Install proper guying to support west span. Maintain a minimum 18' anchor separation from the pole.	0008204
7/14/2024	3/13/22	CEGRW	VIO4936848	330 32ND ST SE	Kent	Wyoming	: KISD to lower stranded attachment a minimum of 2'4" to allow comms space to correct midspan separation violations. Maintain a minimum of 15'6" attachment and midspan ground clearance	0655774
7/14/2024	3/13/22	CEGRW	VIO5007974	3 Poles East of 2525 Leonard St NE	Kent	Grand Rapids	KISD lower attachments at least 5" to fix a 12" at pole separation with US Signal. Maintain a 15'6" at pole and midspan ground clearance.	0923909
7/14/2024	3/20/22	CEHST	VIO5015843	1 Span S. of 3800 Bender Rd	Barry	Middleville	Kent ISD to extend downguy lead to at least 23' to fix downguy failure @ 124% as is.	0436084
7/14/2024	4/7/22	CEGRW	VIO3362064	1P NE of 2346 ELLIOTT ST SE	Kent	Grand Rapids	: KENT ISD to lower attachments at least 4" to allow US Signal too lower attachment above. Maintain a 15'6" at pole and midspan ground clearance.	0642618
7/14/2024	4/23/22	CEGRW	VIO5044610	POLE SVCING 124,128 48TH ST SE	Kent	Kentwood	: KISD to Lower mainline a minimum of 8" to correct 12" attachment separation violation with MCI METRO. Re-sag mainline to maintain a minimum of 15'6" midspan ground clearance in West span.	1596817
7/14/2024	4/28/22	CEGRW	PT4773909	2492 KNAPP ST NE	Kent	Grand Rapids	After CE work, KISD to transfer to new pole. Maintain 40" separation and 30" midspan separation below Consumers, maintain minimum 15'6" ground clearance	CE ID# 0660214
7/14/2024	6/17/22	CEGRW	PT3769430	1825 Leonard St NE	Kent	Grand Rapids	: KISD to lower attachment a minimum 16" to correct 12" at pole separation from US Signal. Maintain 15' 6" at pole ground clearance and 15' 6" midspan ground clearance in all directions	1284635
7/14/2024	7/3/22	CEGRW	VIO3751922	1517,1519,1525,1510 SHERMAN ST SE	Kent	Grand Rapids	KISD TO LOWER ATTACHMENT A MINIMUM OF 5" TO ALLOW AT&T TO LOWER ATTACHMENT. MAINTAIN 15'6" GROUND CLEARANCE.	0440550
7/14/2024	7/28/22	CEGRW	VIO5007991	5 Poles East of 2525 Leonard St NE	Kent	Grand Rapids	: KISD lower attachment at least 4" to fix a 12" at pole separation with US Signal above. Maintain a 15'6" at pole and midspan ground clearance West. Maintain a 18'0" midspan ground clearance East	0923908
7/14/2024	9/17/22	CEGRN	VIO5232867	1 Span W of 505 10 Mile Rd	Kent	Plainfield	Kent ISD: Transfer to pole. Maintain a 12" at pole separation and 6" midspan separation below Charter. Maintain a 16' 0" midspan ground clearance to allow room for applicant to attach.	0663382
7/14/2024	10/15/22	CEGRW	VIO4505783	4948 BURINGAME AVE SW	Kent	Wyoming	KISD to lower 11" to correct a 12" streetlight separation violation. Maintain a minimum of 12" on pole and 6" midspan separation above KEPS	0642384
7/14/2024	12/16/22	CEGRW	VIO5351583	2215 Leonard St NE (Pole W of Pole Servicing)	Kent	Grand Rapids	KISD to lower 11" to correct a 12" streetlight separation violation. Maintain a minimum of 12" on pole and 6" midspan separation above KEPS	0662006
7/14/2024	12/16/22	CEGRW	VIO5351592	1961 Leonard St NE (3 Poles E of Pole Servicing)	Kent	Grand Rapids	KENT ISD to lower attachment a minimum of 12" to allow US Signal to lower. Maintain 15' 6" midspan ground clearance in both directions.	0662003
7/14/2024	12/16/22	CEGRW	VIO5351604	1961 Leonard St NE (Pole Servicing)	Kent	Grand Rapids	: KENT ISD to lower attachment a minimum of 4" to correct 12" at pole separation from US Signal. Maintain 15' 6" midspan ground clearance in all directions	0008162
7/14/2024	12/16/22	CEGRW	VIO5351606	1949 Leonard St NE (Pole W of Pole Servicing)	Kent	Grand Rapids	: KISD to transfer attachment to new pole a minimum of 12" below US Signal. Maintain 6" midspan separation from US Signal while maintaining 15' 6" at pole clearance and 15' 6" midspan ground clearance.	0008173
7/14/2024	1/7/23	CEGRW	VIO4659662	2660 LEONARD ST NE	Kent	Grand Rapids	KISD lower attachment a minimum of 20" to correct the 6" midspan separations in the Northwest span and to make room for Metro Fibernet to attach above. Maintain a minimum 15'6" midspan ground clearance.	0096620
7/14/2024	5/11/23	CEGRW	VIO3670270	2405 Leonard St NE	Kent	Grand Rapids	Kent ISD to lower stranded attachment a minimum of 6" to correct 12" attachment separation violation with US Signal, adjust sag as needed to maintain minimum 15'6" midspan ground clearance, maintain minimum 6" midspan separation below US Signal.	0008171

7/14/2024	6/3/23	CEGRW	VIO4400576	616 GIDDINGS AVE SE	Kent	Grand Rapids	KISD: Lower attachment a minimum of 26" to allow top comms to lower to correct at pole separation violations. Maintain 12" at pole separation and 6" midspan separation above MCI.	1197347
7/14/2024	6/18/23	CEGRW	VIO3751925	1411 Sherman St Se	Kent	Grand Rapids	KISD TO LOWER ATTACHMENT A MINIMUM OF 5" TO CORRECT 12" SEPARATION VIOLATION . MAINTAIN 15'6" GROUND CLEARANCE.	1197333
7/14/2024	6/23/23	CEGRW	VIO3756871	2481 Burlingame Ave SW	Kent	Wyoming	: KISD to lower at least 2'0". Maintain at least 15'6" midspan ground clearance.	0832064
7/14/2024	6/24/23	CEGRW	VIO5599392	2 Poles West of Pole Feeding 1500 Burton St SW	Kent	Wyoming	KISD to remove from ACD Net anchor and attach to own anchor that is already existing. Change anchor lead west from 18' to 17' to fix a 3' anchor separation violation with ACD Net. Maintain a 5' anchor to pole separation.	0869340
7/14/2024	6/24/23	CEGRW	VIO5599417	1 Pole W Of Pole Servicing 1537 Burton St SW	Kent	Wyoming	: Kent ISD to lower attachment at least 16" fix a 12" at pole separation violation with Comcast and to allow them to lower on pole. Maintain a 15'6" at pole and midspan ground clearance.	0024921
7/14/2024	7/8/23	CEGRW	VIO5612868	2 Poles W of Pole SVC 2851 Prairie St. SW	Kent	Wyoming	KISD: LOWER ATTACHMENT A MINIMUM OF 5" TO ALLOW SPACE FOR EVERTSREAM TO PROPERLY ATTACH TO POLE ABOVE. MAINTAIN A MINIMUM 16'0" ATTACHMENT AND 15'6" GROUND CLEARANCE.	0024931
7/14/2024	7/8/23	CEGRW	VIO5612880	1 Pole W of Pole SVC 2969 Prairie St. SW	Kent	Grandville	Kent ISD: Lower attachment a minimum of 12" to correct 6" midspan separation violation E. Maintain 6" midspan separation below Everstream. Maintain 15'6" midspan ground clearance.	0037528
7/14/2024	7/26/23	CEGRW	VIO3738568	2434 & 2431 LAKE DR SE	Kent	East Grand Rapids	KISD to lower attachment at least 12" to fix a 12" at pole and 6" midspan separation violation going north west with EGRPS. Maintain a 15'6" at pole and midspan ground clearance.	0818976
7/14/2024	8/7/23	CEGRW	VIO3767148	2025 Leonard St NE	Kent	Grand Rapids	Lower the Kent ISD attachment a minimum 4" to allow US Signal to lower. Maintain a minimum 15'6" midspan ground clearance.	CE ID# 0008172
7/14/2024	8/18/23	CEGRW	VIO5669383	Pole Servicing 2605 60th St SE	Kent	Grand Rapids	: KENT ISD (KISD) Lower attachment a minimum 3'0" to correct 12" at pole separation violation and to allow room for comms above to correct violations. Maintain a minimum 15'6" midspan ground clearance	0151529
7/14/2024	8/18/23	CEGRW	VIO5669395	1 Pole Northwest of Pole Servicing 2626 60th St SE	Kent	Grand Rapids	KENT ISD (KISD) Lower attachment a minimum 1'8" to correct 6" midspan separation violation east. Maintain a minimum 15'6" midspan ground clearance	1288185
7/14/2024	8/18/23	CEGRW	VIO5669406	1 Pole North of Pole Servicing 2700 60th St SE	Kent	Grand Rapids	KENT ISD (KISD) Lower attachment 1'9" to allow to comm to correct violations and to allow room for applicant to attach to pole. Maintain a minimum 15'6" midspan ground clearance	0151527
7/14/2024	8/18/23	CEGRW	VIO5669412	1 Pole East of Pole Servicing 3182 60th St SE	Kent	Grand Rapids	KENT ISD (KISD) Lower attachment a minimum 2'0" to allow room for top comm to correct violations. Maintain a minimum 15'6" midspan ground clearance	0154026
7/14/2024	9/8/23	CEGRE	VIO5700897	Pole Servicing 2383 Pettis Ave	Kent	Grand Rapids	: KISD Lower attachment and guy stand a minimum 5" to correct 12" at pole separation violation. Maintain a minimum 15'6" midspan ground clearance.	0909960
7/14/2024	10/6/23	CEGRW	VIO5730386	1 Pole east of Pole Servicing 1990 Robinson Rd SE	Kent	Grand Rapids	: Kent ISD: Coordinate with AT&T and lower attachment a minimum 1'6" to correct a 12" separation violation. Maintain a 15'6" midspan ground clearance.	0110534
7/14/2024	10/6/23	CEGRW	VIO5730391	Pole Servicing 1905 Woodward Ln SE	Kent	Grand Rapids	KENT ISD: Lower attachment a minimum 1'1" to allow room for comms to lower. Maintain a 15'6" midspan ground clearance	0039218
7/14/2024	10/6/23	CEGRW	VIO5730426	1 Pole East and 1 Pole North of Pole Servicing 201 Woodward Ln SE	Kent	Grand Rapids	: Kent ISD: Lower attachment a minimum 1'11" to correct a 12" separation violation. Maintain a 12" at pole separation and a 6" midspan separation below AT&T.	0039221
7/14/2024	10/7/23	CEGRW	VIO5642627	2277 DEAN LAKE AVE NE	Kent	Grand Rapids	KENT ISD to attach to pole with minimum of 12" at pole separation and 6" midspan separation below Comcast. Maintain a 15'6" midspan ground clearance.	1976264
7/14/2024	11/15/23	CEGRW	VIO5669391	1 Pole Northwest of Pole Servicing 2626 60th St SE	Kent	Grand Rapids	KENT ISD (KISD) Lower attachment a minimum 1'8" to correct 6" midspan separation violation east. Maintain a minimum 15'6" midspan ground clearance.	1288185
7/14/2024	11/19/23	CEGRW	VIO3682541	1249 36TH ST SW	Kent	Wyoming	KISD to lower a minimum of 7" to correct 12" attachment separation violation and 6" midspan separation violation. Maintain a minimum of 15'6" midspan ground clearance	CE ID#0539526
7/14/2024	11/22/23	CEGRW	VIO5815225	1299 36th St	Kent	Wyoming	KISD to lower a minimum of 11" to make room for MCI Metro to lower. Maintain a minimum of 15'6" midspan ground clearance.	CE ID# 0535522
7/14/2024	11/26/23	CEGRW	VIO5824194	1985 Aberdeen St NE	Kent	Grand Rapids	: KENT ISD to lower a minimum of 12" on the pole to partially correct 30" midspan separation East. Maintain minimum 15'6" midspan ground clearance.	0663153

7/14/2024	11/26/23	CEGRW	VIO5824208	1985 Aberdeen St NE	Kent	Grand Rapids	KENT ISD to lower a minimum of 1'10" on the pole to fix 12" at pole separation violation, 6" midspan separation violation East and West, and allow above comms room to lower. Maintain minimum 15'6" midspan ground clearance. KENT ISD to install down guy/anchor 5' North to support line angle. Maintain a 3' anchor to anchor separation. Do not cross other down guys.	0660235
7/14/2024	11/26/23	CEGRW	VIO5824523	2277 Dean Lake Ave NE	Kent	Grand Rapids	KENT ISD to lower a minimum of 1'5" to allow room for Comcast to lower. Maintain a 15'6" midspan ground clearance	0660227
7/14/2024	12/2/23	CEGRW	VIO5835883	UNK Elliott St SE	Kent	Grand Rapids	KISD to lower a minimum 7" to correct a 12" attachment violation. Maintain a minimum 15'6" midspan ground clearance	CE ID#: 0642620
7/14/2024	12/2/23	CEGRW	VIO5837159	1766 Breton Rd SE	Kent	Grand Rapids	: KISD to lower a minimum 12" to correct a 6" midspan separation violation. Maintain a minimum 15'6" midspan ground clearance	CE ID#: 0093984
7/14/2024	1/18/24	CEGRW	PT4809063	917 Aberdeen St NE	Kent	Grand Rapids	: KISD transfer to new pole. Maintain at least 12" attachment separation and 6" midspan separation below AT&T, and 15'6" midspan ground clearance.	CE ID# 0662724
7/14/2024	1/27/24	CEGRE	VIO5913329	3730 Knapp St NE	Kent	Grand Rapids	C : Kent ISD Lower attachment a minimum of 6" to allow room for other communications to lower. Maintain minimum 15'6" midspan ground clearances	0987638
7/14/2024	2/3/24	CEGRW	VIO5729004	2 Poles West of Pole Servicing 1830 Robinson Rd SE	Kent	Grand Rapids	: KENT ISD: Lower attachment a minimum 4" to correct 12" separation violation. Maintain a 12" at pole separation and a 6" midspan separation below AT&T. Maintain a 15'6" midspan ground clearance. Reduce anchor lead a minimum 3" to allow room for comms to reduce leads. Maintain a 5' pole separation.	0039211
7/14/2024	2/7/24	CEGRW	VIO3715072	3208 Badger Ave SW	Kent	Wyoming	: Lower Kent ISD a minimum of 12" to allow Comcast to lower and to correct 6" midspan separation violation with Comcast. Maintain a minimum 15'6" ground clearance.	0894254
7/14/2024	2/8/24	CEGRW	VIO3772787	3200 32nd ST SW	Kent	Grand Rapids	KISD TO LOWER AT LEAST 12" TO CORRECT 12" SEPARATION VIOLATION WITH AT&T AND 6" MIDSPAN SEPARATION VIOLATION IN THE EAST SPAN WITH COMCAST. MAINTAIN AT LEAST 15'6" GROUND CLEARANCE	CEID# 0894294
7/14/2024	2/15/24	CEGRN	VIO5932670	5255 Alpine Avenue Northwest	Kent	Alpine	: KISD extend north down guy at least 6' to correct guy strand crossing violation. Maintain 3' anchor separation outside MDOT guying..	CE ID# 0657447
7/14/2024	2/15/24	CEGRN	VIO5934206	4855 Alpine Avenue Northwest	Kent	Alpine	KISD lower attachment at least 2'0" to allow comm above to lower. Maintain 15'6" minimum ground clearance. (to lower on pole to south)	CE ID# 1714634
7/14/2024	2/15/24	CEGRN	VIO5934220	4855 Alpine Avenue Northwest	Kent	Alpine	KISD lower attachment at least 2'0" to allow comm above to lower. Maintain 15'6" minimum ground clearance. (to lower on pole to north & south).	CE ID# 1714622
7/14/2024	2/15/24	CEGRN	VIO5934231	841 Alpine Church Road Northwest	Kent	Alpine	: KISD lower attachment at least 2'0" to obtain 6" midspan separation from MCI and allow them to lower. Maintain 15'6" minimum ground clearance, with 18'0" minimum ground clearance over road. (to lower on pole to north)	CE ID# 0537454
7/14/2024	2/17/24	CEGRW	VIO3766278	4125 BURLINGAME AVE SW	Kent	Grand Rapids	: KISD to lower 8" to correct a 12" attachment separation violation with CE down guy. Maintain 12" attachment and 6" midspan separation above ACD NET.	CE ID#0474450
7/14/2024	2/18/24	CEGRW	PT3833461	7909 BURLINGAME AVE SW	Kent	Byron	: KISD to transfer to new pole. Maintain minimum 12" attachment and 6" midspan separation below BC PS and minimum 15'6" midspan ground clearance.	CE ID# 1193832
7/14/2024	2/18/24	CEGRW	PT4821521	7987 BURLINGAME AVE SW	Kent	Byron	KISD to transfer to new pole. Maintain minimum 12" attachment and 6" midspan separation below BC PS and minimum 15'6" midspan ground clearance.	CE ID: 0152388
7/14/2024	2/18/24	CEGRW	VIO5381444	8246 Burlingame Ave SW	Kent	Byron	Kent ISD to attach to pole and maintain a 12" at pole separation and 6" midspan separation below Byton Center ISD	1277173
7/14/2024	2/18/24	CEGRW	VIO5869360	2162 36th St SW	Kent	Wyoming	KISD to lower line a minimum of 28" to help correct 6" midspan separation violation and allow comms above to lower out of violations. Maintain a minimum 12" attachment and 6" midspan separation above MCI Metro.	0748312
7/14/2024	2/24/24	CEGRW	VIO3754330	3273 PRAIRIE ST SW	Kent	Grandville	KISD TO LOWER AT LEAST 12" TO CORRECT ATTACHMENT AND MIDSPAN SEPARATION VIOLATIONS. MAINTAIN AT LEAST 12" ATTACHMENT AND 6" MIDSPAN SEPARATION BELOW 123NET AND 15'6" MIDSPAN CLEARANCE	CE ID# 0473432
7/14/2024	2/24/24	CEGRW	VIO3759365	3325 MICHAEL AVE SW	Kent	Wyoming	KISD TO LOWER AT LEAST 36" TO ALLOW COMMS TO LOWER. MAINTAIN AT LEAST 15'6" GROUND CLEARANCE	CEID#0547033
7/14/2024	2/24/24	CEGRW	VIO5257592	1006 32nd St SW	Kent	Wyoming	: KISD TO LOWER AT LEAST 12" TO ALLOW ABOVE COMMS TO LOWER. MAINTAIN AT LEAST 15'6" GROUND CLEARANCE	CEID#0538129

7/14/2024	2/25/24	CEGRW	VIO3353385	3299 PRAIRIE ST SW	Kent	Grandville	KISD TO RAISE AT LEAST 4" TO CORRECT GROUND CLEARANCE VIOLATION, MAINTAIN AT LEAST 12" ATTACHMENT. 6" MIDSPAN SEPARATION BELOW 123NET AND 15'6" MIDSPAN GROUND CLEARANCE	CE ID# 0473433
7/14/2024	2/25/24	CEGRW	VIO5961181	3311 WOODBINE AVE SW	Kent	Grandville	KISD TO LOWER AT LEAST 4" TO CORRECT ATTACHMENT SEPARATION VIOLATION. MAINTAIN AT LEAST 12" ATTACHMENT, 6" MIDSPAN SEPARATION BELOW 123NET AND 15'6" MIDSPAN GROUND CLEARANCE	0473434
7/14/2024	2/29/24	CEGRW	VIO3454236	1985 Aberdeen St NE	Kent	Grand Rapids	KENT ISD to lower a minimum of 4'1" on the pole to fix 30" midspan separation violation West, 6" midspan separation violation East, and allow above comms room to lower. Maintain minimum 15'6" midspan ground clearance	0660236
7/14/2024	3/1/24	CEGRW	VIO3731311	KNAPP ST NE	Kent	Grand Rapids	: KISD to install a guy to the W to support the deadend attachment. Re-sag the E span as needed to correct the ground clearance violation. Maintain a minimum of 15'6" ground clearance	0987565
7/14/2024	3/1/24	CEGRW	VIO3731373	3238 KNAPP ST NE	Kent	Grand Rapids	: KISD to lower on pole a minimum of 1' to allow City of Grand Rapids to lower. Maintain a minimum of 15'6" ground clearance	0058506
7/14/2024	3/1/24	CEGRW	PT3731390	KNAPP ST NE	Kent	Grand Rapids	: KISD to attach directly to the pole at current height. Maintain a minimum of 12" on pole and 6" midspan separation below City of GR. Maintain a minimum of 15'6" ground clearance.	0987568
7/14/2024	3/1/24	CEGRW	VIO3731404	KNAPP ST NE	Kent	Grand Rapids	KISD to lower a minimum of 1' on pole to allow City of GR to lower. Maintain a minimum of 15'6" ground clearance. Move guy lead to a minimum of 3' inside of the Comcast guy, while also maintaining a minimum of 5' from the base of the pole	0987569
7/14/2024	3/1/24	CEGRW	VIO3754201	3284 KNAPP ST NE	Kent	Grand Rapids	KISD to lower a minimum of 1'4" on pole to correct the 12" on pole separation violation with City of GR. Maintain a minimum of 12" on pole and 6" midspan separation below City of GR. Maintain a minimum of 15'6" ground clearance.	0987566
7/14/2024	3/1/24	CEGRW	VIO5976220	3255 MICHAEL AVE SW	Kent	Wyoming	: KISD TO LOWER AT LEAST 24" TO ALLOW COMMS TO LOWER. MAINTAIN AT LEAST 15'6" GROUND CLEARANCE	CEID#0538107
7/14/2024	3/1/24	CEGRW	VIO5976296	3313 AND 3317 MICHAEL AVE SW	Kent	Wyoming	: KISD TO LOWER AT LEAST 24" TO ALLOW COMMS TO LOWER. MAINTAIN AT LEAST 15'6" GROUND CLEARANCE.	CEID#0833876
7/14/2024	3/6/24	CEGRW	VIO5987739	3255 KNAPP ST NE	Kent	Grand Rapids	KISD to lower on pole a minimum of 2'4" to correct the on pole separation violation with City of Grand Rapids and to allow City of Grand Rapids to lower. Maintain a minimum of 12" on pole above the AT&T Control Box. Maintain a minimum of 15'6" ground clearance.	0058508
7/14/2024	3/21/24	CEGRW	VIO6014598	1 POLE S OF POLE SVCING 4253(UG) DIVISION AVE S	Kent	Wyoming	: KISD TO LOWER ATTACHMENT A MINIMUM OF 18" TO CORRECT 6" MIDSPAN SEPARATION VIOLATION WITH ITP IN NORTH SPAN AND ALLOW ROOM FOR COMMS ABOVE TO LOWER AND CORRECT VIOLATIONS. MAINTAIN A MINIMUM OF 15'6" MIDSPAN GROUND CLEARANCE	0114048
7/14/2024	3/24/24	CEGRW	VIO6020025	N/A MURRAY ST SW	Kent	Wyoming	: LOWER ATTACHMENT A MINIMUM OF 18" TO ALLOW COMMS ABOVE TO CORRECT 40" SAFETY ZONE VIOLATION. MAINTAIN A MINIMUM 16'0" ATTACHMENT AND 15'6" GROUND CLEARANCE IN THE MIDSPAN	0114051
7/14/2024	3/24/24	CEGRW	VIO6020033	4336 DIVISION AVE S	Kent	Wyoming	: LOWER ATTACHMENT A MINIMUM OF 4" TO CORRECT 12" ATTACHMENT SEPARATION VIOLATION. MAINTAIN A MINIMUM OF 12" ATTACHMENT AND 6" MIDSPAN SEPARATION BELOW INTER URBAN RAPID TRANSIT. MAINTAIN A MINIMUM 16'0" ATTACHMENT AND 15'6" MIDSPAN GROUND CLEARANCE	0114049
7/14/2024	3/24/24	CEGRW	VIO6023271	4157 Division Ave S	Kent	Wyoming	KISD to lower a minimum 10" to allow other comms to lower out of violations. Maintain a minimum 15'6" midspan ground clearance.	0114042
7/14/2024	3/28/24	CEGRW	VIO6034966		Kent	Grand Rapids	: KISD to lower at least 1'0" to make space for comms above to lower. Maintain at least 15'6" ground clearance.	0402502
7/14/2024	3/28/24	CEGRW	VIO6035162		Kent	Grand Rapids	: KISD to lower at least 1'0" to correct 12" attachment separation violation and to make space for comms above to lower. Maintain at least 15'6" ground clearance	0402672
7/14/2024	4/6/24	CEGRW	PT5351677	2147 Leonard St NE (Pole Servicing)	Kent	Grand Rapids	KISD to transfer attachment to new pole a minimum of 12" below AT&T. Maintain 6" midspan separation from AT&T while maintaining 15'6" at pole clearance and 15'6" midspan ground clearance.	0008185
7/14/2024	4/18/24	CEHAM	VIO5942124	1035 ABERDEEN ST NE,	Kent	Grand Rapids	KENT ISD Lower attachment a minimum of 33" to allow AT&T to lower attachment. Maintain a minimum of 15'6" midspan ground clearances.	0662758
7/14/2024	4/18/24	CEGRN	VIO6058096		Kent	Ada	KISD to lower at least 12" to make space for comms above to lower. Maintain at least 15'6" ground clearance. Note: raising on adjacent pole to the west to maintain ground clearance	0909963

7/14/2024	4/18/24	CEGRN	VIO6058102		Kent	Ada	KISD to lower at least 12" to make space for comms above to lower. Maintain at least 15'6" ground clearance. Note: raising on adjacent pole to the west to maintain ground clearance	0909961
7/14/2024	5/5/24	CEGRE	VIO4116260	6450 HANNA LAKE AVE SE	Kent	Caledonia	: KISD to raise mainline a minimum of 3'2" to allow AT&T to also raise to correct the existing midspan ground clearance violations. Maintain a minimum 52" attachment separation & 36" midspan separation below CE neutral to allow METRONET to attach above	0930680
7/14/2024	5/9/24	CEGRW	PT5824543	2277 DEAN LAKE AVE NE	Kent	Grand Rapids	: KENT ISD transfer to new pole with minimum 12" comm separation on the pole and 6" separation at the midspan below Comcast. Maintain minimum 15'6" midspan ground clearance	0660230
7/14/2024	5/11/24	CEGRW	VIO5774237	36 ST SE	Kent	Grand Rapids	KISD to lower at least 3'0" to allow other comms to lower . Maintain at least 15'6" midspan ground clearance	CE ID: 0098498
7/14/2024	5/17/24	CEGRW	VIO3442955	1261 Aberdeen St	Kent	Grand Rapids	Kent ISD to raise a minimum of 1'4" to allow the applicant to attach. Maintain a minimum 12" separation and a 6" midspan separation below Comcast.	CE ID# 0663115
7/14/2024	5/18/24	CEGRW	VIO6083434	Pole Servicing 19 Plymouth Ave NE	Kent		KENT ISD Lower attachment a minimum 11" to correct 12" at pole separation violation. Maintain a minimum 15'6" midspan ground clearance	0823113
7/14/2024	5/18/24	CEGRW	VIO6084162	Pole Servicing 111 Plymouth Ave NE	Kent		KENT ISD Lower attachment a minimum 2'4" to allow room for comms above to correct violations. Maintain a minimum 15'6" midspan ground clearance	0823121
7/14/2024	5/18/24	CEGRW	VIO6090990	Pole Servicing 333 Plymouth Ave NE	Kent		: KENT ISD Lower attachment a minimum 1'4" to allow room for comms above to correct violations, Maintain a minimum 15'6" midspan ground clearance	0833085
7/14/2024	5/31/24	CEGRW	VIO3489949	6389 64TH ST SW	Kent	Byron	KISD TO RAISE AT LEAST 2'2 TO ALLOW COMCAST TO RAISE OUT OF VIOLATIONS. MAINTAIN A MINIMUM OF 52" ATTACHMENT AND 36" MID SPAN SEPARATION BELOW CONSUMERS TO ALLOW ROOM FOR METRONET.	CE ID # 0417924
7/14/2024	6/1/24	CEGRW	VIO3771800	5910 BURLINGAME AVE (UG)	Kent	Wyoming	KISD attach mainline attachment to pole. Maintain a minimum 52" attachment separation and 36" midspan separation below CE to allow room for applicant to attach above	1288910
7/14/2024	6/19/24	CEGRW	VIO6148495	6149 Burlingame Ave SW	Kent	Wyoming	KISD to raise mainline attachment a minimum of 7" to allow room for Everstream to raise and correct a 12" attachment separation. Maintain a minimum 52" attachment separation below CE and a 36" midspan separation below CE to allow room for applicant to attach above	1342727
7/14/2024	6/19/24	CEGRW	VIO6149198	5991 Burlingame Ave SW	Kent	Wyoming	KISD to raise mainline attachment a minimum of 7" to allow room for Everstream to raise and correct a 12" attachment separation. Maintain a minimum 52" attachment separation below CE and a 36" midspan separation below CE to allow room for applicant to attach above.	0417933
7/14/2024	6/19/24	CEGRW	VIO6149227	5975 Burlingame Ave SW	Kent	Wyoming	KISD to lower mainline attachment a minimum of 4" to allow room for applicant to attach above. Maintain a minimum 12" attachment separation and 6" midspan separation above Everstream.	0752289
7/14/2024	6/21/24	CEGRW	VIO6176242	1 Pole East of Pole Feeding 1500 Burton St SW	Kent	Wyoming	KENT ISD to lower a minimum of 1' to fix 12" pole separation violation with Comcast. Maintain minimum 12" separation on the pole and 15' 6" minimum ground clearance	0024921
7/14/2024	6/21/24	CEGRW	VIO6176257	1 Pole South of Pole Servicing 1503 Burton St SW	Kent	Wyoming	KENT ISD to attach to pole at maximum 18' 8" and maintain 15' 6" ground clearance	0441353
7/14/2024	6/21/24	CEGRW	VIO6176286	1414 Burton St SW	Kent	Wyoming	KENT ISD to attach to pole at maximum 18' 8" and maintain 15' 6" ground clearance	0098966
7/14/2024	6/30/24	CEGRE	PT4116252	SE OF 6375 HANNAH LAKE AVE SE	Kent	Grand Rapids	After CE performs required work, KISD to lower mainline a minimum of 1'4" to allow COMCAST to also lower. Maintain a minimum 16" attachment separation below COMCAST & a minimum 15'6" midspan ground clearance in both spans.	0443187
7/14/2024	7/11/24	CEGRW	PT5390409	3305 Burlingame Ave SW	Kent	Wyoming	KENT ISD Transfer attachment to new pole. Maintain a minimum 12" at pole separation below comm above and a minimum 6" midspan separation below comm above	1172728