

ESTIMATE

THIS ESTIMATE IS VALID FOR THIRTY (30) DAYS.
CLEAR-ARMOR LAMINATES ARE CUSTOM CUT TO ORDER.



Estimate #	37255
Date	9/30/2025
Rep	

32991 North Thornapple Ln.
Grayslake, IL 60030
Office: (847) 665-8447
Fax: (847) 223-2445

Billing Address

Crosslake Community School
35808 County Rd 66
Crosslake, MN 56442

Install Address

Interior Doors

BALANCE DUE UPON COMPLETION OF JOB. ALL SALES ARE FINAL.

Total SqFt 134.80

Product/Service	Description	SubTotal:
15mil	15 mil laminate will create a smash/burglar/bomb and strong-wind resistant environment.	4,313.60
Travel & Crew Expenses	Included	
Installation	Price reflects a turn key installation.	
Caulk	Included	

Disclaimer: If client or contact person not available for final walk-through and the job has been satisfactorily completed, signature of Clear-Armor crew leader will be sufficient for conclusion of the project.

Total Price: \$4,313.60

Signature: _____ >This estimate becomes a binding contract upon signature.

Clear-Armor, LLC, shall be entitled to recover any sustained costs and/or fees, including, but not limited to, any reasonable attorney's fees which may be incurred while attempting to obtain any such relief in connection with this Agreement. In the event of any litigation which may be related to this Agreement if Clear-Armor, LLC prevails, it shall be entitled to recover any such reasonable attorney's fees and expenses incurred.

This Agreement shall be governed and construed in accordance with the laws of the State of Illinois or any applicable federal laws or statutes, applicable to contracts made within such state, without giving effect to any form of conflict of law provisions thereof. The Federal and State courts located in the State of Illinois shall have sole and exclusive jurisdiction over any disputes arising under the terms of this Agreement.

Clear Armor laminates are the only security films to have exceeded the ULC-S332-93 (Standard for Burglary and Resistant Glazing Material) & ANSI Z97 on 1/8" inch glass. Our SL 15 three ply laminate is bullet resistant when applied on 1/2" inch glass. For optimal performance, CLEAR ARMOR recommends that all tempered glass be replaced with regular annealed glass when possible. Safety Films/Security Laminates are a deterrent and may not prevent ultimate entry.

Since laminates and films are applied with a water-based solution, it is normal for minor bubbling and hazing to occur during installation before curing. This curing period will vary in time depending on the level of exposure to direct sunlight, time, and thickness of laminate. Although this curing process is minimal (30 days or less) on thinner films, it could extend beyond 6 months on thicker laminates that are installed on interior glass. All moisture and water bubbles will disappear with time as the moisture evaporates through the multiple layers of polyester. CLEAR ARMOR will take every necessary action possible to clean all windows prior to the installation of the laminate; minor dust particles may appear after the installation of the laminate as a result of airborne dust. These particles will dissipate with time and should not be visible when looking through the glass at a distance of 6 feet. (Ask for further details) VS:8: SEP 1815