201 North Harrison Street Geneva, Illinois 60134 (630) 463-3300



Harrison Street Elementary School

We are self-directed, lifelong learners; effective communicators; complex, creative, & adaptive thinkers; and collaborative & productive citizens.

TO: Dr. Dean Romano

FROM: Brenna Westerhoff

RE: Gifts, Grants, and Bequests

DATE: April 8, 2019

Dr. Romano,

In accordance with Policy 7230 - Gifts, Grants, and Bequests having a value of more than \$500.00 shall be accepted by the Board of Education.

The Girl Scout Troop #231 would like to donate a water fountain and bottle filling station to Harrison Street Elementary School.

The total value of this donation is \$3,356 plus freight.

I am requesting approval from the Board of Education, at their regularly scheduled meeting, Monday, April 8, 2019, to accept the donation from Girl Scout Troop #231 for \$3,356 plus freight.



Elkay EZH2O Vandal-Resistant Bottle Filling Station & Bi-Level Cooler Non-Filtered 8 GPH Stainless

Model VRCTL8WSK

'RODUCT SPECIFICATIONS

Elkay ezH2O® Vandal-Resistant Bottle Filling Station, & Bi-Level Cooler, Non-Filtered 8 GPH Stainless. Chilling Capacity of 8.0 GPH gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Green Ticker™, Laminar Flow, Real Drain, Vandal-Resistant. Furnished with Vandal-Resistant bubbler. Electronic Bottle Filler Button With Aechanical Front Bubbler Button activation. Product shall be Wall All All Mount (On-Wall), for Indoor/Outdoor applications, serving 2 station(s). Init shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit thall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead ree) and meets Federal and State low-lead requirements.

	14
pecial Features:	Green Ticker™, Laminar Flow, Real Drain, Vandal-Resistant
inish:	Stainless Steel
ower:	115V/60Hz
lubbler Style:	Vandal-Resistant
ctivation by:	Electronic Bottle Filler Button With
	Mechanical Front Bubbler Button
flounting Type:	Wall Mount (On-Wall)
:hilling Option*:	8.0 GPH
ull Load Amps	1
lated Watts:	370
limensions (L x W x H):	36-1/8" x 18-5/8" x 38-13/16"
pprox. Shipping Weight:	118 lbs.
nstallation Location:	Indoor/Outdoor
lo. of Stations Served:	2
Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled	

Mechanically-Activated bubbler continues to supply water in event of service disruptions.

Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.

Laminar flow provides clean fill with minimal splash.

Real Drain System eliminates standing water.

Vandal-resistant, bubblers are one-piece, chrome plated with integral hood guard design to prevent contamination from other users, airborne deposits and tampering.

COOLING SYSTEM

rinking water.

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	



AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and

endure. For almost a century, Elkay has been a family-owned an operated company, providing thousands of jobs that support our families and communities.



Included with Product:

Water Cooler (VRCTL8WSC), Bottle Filler (VRCWS)

▼ Ships in multiple boxes.

PRODUCT COMPLIANCE

ADA & ICC A117.1

Buy American Act

CAN/CSA C22.2 No. 120

GreenSpec®

NSF/ANSI 61 & 372 (lead free)

UL 399







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF)

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

OPTIONAL ACCESSORIES

EWF3000 - WaterSentry Plus Filter System Kit (Bottle Fillers)
98324C - Cane Apron for HAC, HVR, EMABF & VRC Models
(Stainless)
36292C - Accessory - Power Block

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.