

CE SCHOOL BUS

Sales Proposal For: Galveston ISD

Presented By: LONGHORN BUS SALES Prepared For: Galveston ISD Mike Praker 3101 83rd st. Galveston, TX 77554-(409)740 - 1208 Reference ID: 2 77P DSL 3PT Presented By: LONGHORN BUS SALES LINDA BLUME 9100 N LOOP E HOUSTON TX 77029 -(713)631-9306

Model Profile 2025 CE SCHOOL BUS (PB110)

| AXLE CONFIG: | 4X2 |
|--------------------------------|---|
| APPLICATION: | School Transportation |
| MISSION: | Requested GVWR: 31000. Calc. GVWR: 31000 |
| | Calc. Start / Grade Ability: 25.81% / 1.83% @ 55 MPH |
| | Calc. Geared Speed: 79.2 MPH |
| DIMENSION: | Wheelbase: 276.00, CA: N/A, Axle to Frame: 166.00 |
| ENGINE, DIESEL: | {Cummins B6.7 240} EPA 2024, 240HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM |
| | Governed Speed, 240 Peak HP (Max), School Bus Only |
| TRANSMISSION, AUTOMATIC: | {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less |
| | PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus |
| CLUTCH: | Omit Item (Clutch & Control) |
| AXLE, FRONT NON-DRIVING: | {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity |
| AXLE, REAR, SINGLE: | {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends Gear Ratio: 6.14 |
| TIRE, FRONT: | (2) 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position |
| TIRE, REAR: | (4) 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position |
| SUSPENSION, REAR, AIR, SINGLE: | {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted |
| | Outside the Rails |
| PAINT: | Cab schematic 100NB |
| | Location 1: 4421, School Bus Yellow (Std) |
| | Chassis schematic N/A |

| <u>Code</u> PB11000 | Description Base Chassis, Model CE SCHOOL BUS with 276.00 Wheelbase, N/A CA, and 166.00 Axle to Frame. |
|------------------------|---|
| BODY PLANS | |
| 47AMG | BODY, BUS Conventional; 78" Headroom, 34'11" Body Length, +9 Section Rear, 81 Passenger, 276 WB |
| | Includes : NOTE: Body Mandates Overall Vehicle Length of Greater than 40 Feet |
| 50ZCZ | BODY PLAN, NON-SPECIAL NEEDS for CE, 34' 11" Body Length, +9 Section Rear, 77 Passenger, 276" WB, DM0080A000 |
| 49001 | BODY PLAN, APPROVED VARIATION Number 001 |
| AXLE CONFIGURAT | ION |
| 1ANA | AXLE CONFIGURATION {Navistar} 4x2 |
| ENGINE | |
| 12EYG | ENGINE, DIESEL {Cummins B6.7 240} EPA 2024, 240HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max), School Bus Only |
| 12VJR | EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2024 |
| 12XCS | CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty |
| 12WZE | CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations |
| 12WVG | EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood |
| 12XCC | RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 SqIn Louvered, with 383 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler |
| | Includes : RADIATOR HOSES Premium, Rubber |
| 12TSY | FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On |
| | Includes : FAN Nylon |
| 12VCE | AIR CLEANER Single Element, Fire Retardant Media |
| 12703 | ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection |
| 12VVN | CRUISE CONTROL Electronic |
| 12VYV | IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package |
| 12WPV | OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines |
| 12UGN | THROTTLE, HAND CONTROL Electronic |
| TRANSMISSION | |
| 13BBP | TRANSMISSION, AUTOMATIC {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus |
| 13WVW | NEUTRAL AT STOP OMIT |
| 13WYY | SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming |

| <u>Code</u> 13WLN | Description TRANSMISSION OIL Synthetic; 20 thru 28 Pints |
|----------------------|--|
| 13WEX | TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series Transmission |
| CLUTCH | |
| 11001 | CLUTCH Omit Item (Clutch & Control) |
| REAR AXLES, SUSPENS | SIONS |
| 14AKC | AXLE, REAR, SINGLE {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends . Gear Ratio: 6.14 |
| 14TDV | SUSPENSION, REAR, AIR, SINGLE {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted Outside the Rails |
| FRONT AXLES | |
| 2ASH | AXLE, FRONT NON-DRIVING {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity |
| FRONT SUSPENSIONS | |
| 3ADB | SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock Absorbers |
| | Includes : SPRING PINS Rubber Bushings, Maintenance-Free |
| CABS, COWLS, BODIES | 3 |
| 16010 | COWL Flat Back |
| 16BAM | AIR CONDITIONER with Integral Heater and Defroster |
| 16VKB | CAB INTERIOR TRIM Classic, for Day Cab |
| 16GEG | GAUGE CLUSTER Premium Level; English with English Electronic Speedometer |
| | Includes : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped) : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped) |
| 16HLJ | GAUGE, DEF FLUID LEVEL |
| 16HGH | GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission |
| 16563 | HEATER SHUT-OFF VALVES (2) Ball Valve Type |
| 16XJP | INSTRUMENT PANEL Wing Panel |
| 16HKT | IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster |
| 16VVJ | WINDSHIELD Three Piece, Bonded, with Shaded Band |
| EDAMES | |

FRAMES

| STEERING | |
|---------------------|---|
| 4WJP | PARKING BRAKE INTERLOCK with Electronic Park Brake, Parking Brake Cannot be Released Until Ignition Switch is in "On" Position and Service Brake Pedal is Applied, Use with Air Brake Chassis Only |
| 4WZT | GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121 Requirements, for Conventional Bus |
| 4722 | DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank |
| 4VLY | AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab |
| 4VLE | AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side |
| 4EDN | AIR DRYER {Bendix AD-9SI} with Heater, Includes Safety Valve |
| 4SPA | AIR COMPRESSOR {Cummins} 18.7 CFM |
| 4LGG | SLACK ADJUSTERS, REAR {Gunite} Automatic |
| 4EXU | BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake |
| 4XDR | BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle |
| 4LAG | SLACK ADJUSTERS, FRONT {Gunite} Automatic |
| 4EXP | BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn |
| 4XDD | BRAKES, FRONT {Meritor 15X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 5", 13,200-lb Capacity |
| 4GBL | BRAKE, PARKING {Bendix Intellipark} Electronic Park Brake, for Truck or Bus Applications |
| 4AZS | AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control |
| | Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6 |
| 4091 | BRAKE SYSTEM, AIR Dual System for Straight Truck Applications |
| BRAKES | |
| 1WJE | WHEELBASE RANGE 276" (700cm) Only |
| 1SAL | CROSSMEMBER, REAR, AF (1) |
| | Includes : CONTROL ASSEMBLY Solid State, Located Rear of Front Bumper, Heater not Required : CROSSING GATE, FRONT Matches Contour of Bumper |
| 1LMW | CROSSING GATE, FRONT Electric, Yellow Blade, Bumper Mounted |
| | <u>Notes</u> : Bumper Thickness is .25" |
| 1LSH | BUMPER, FRONT Contoured, Steel, Naviflex Spray on Coating, Severe Duty |
| <u>Code</u> 1CAC | Description FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL |

| <u>Code</u> | Description |
|-------------|-------------------------------------|
| 5PSA | STEERING GEAR {Sheppard M100} Power |

5708 STEERING COLUMN Tilting

5CAW STEERING WHEEL 4-Spoke; 18" Dia., Black

DRIVELINES

| 6DGA | DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2 |
|------|--|
|------|--|

6901 PROPSHAFT GUARD

EXHAUST SYSTEMS

| 7ВМК | EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long Horizontal Tail Pipe |
|------|---|
| 7SCP | ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger |
| 7WCX | HEAT SHIELD Between Exhaust & Fuel Tank, Mounted to AF Crossmember |
| 7WBL | TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper |

ELECTRICAL SYSTEMS

| ELECTRICAL SYSTEM 12-Volt, Standard Equipment |
|---|
| Includes : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WIRING, CHASSIS Color Coded and Continuously Numbered |
| ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote Sense |
| ANTENNA Shark Fin, Roof Mounted |
| BATTERY BOX Steel, with Powder Coat Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted Left Side Behind Front Axle Perpendicular to Frame Rail |
| BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud |
| BK WARN IND,PARK BK NOT SET Visual and Audible Alarm, Active Upon Ignition Off and Parking Brake No Set, Reminder to Set Parking Brake |
| CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses |
| CLOCK Digital, White LED Lettering, Black Background, Black Bezel, 12 Hour Clock Format, Western Arial Font Digital Readout, Display Dims by 50% When Headlights Are On, Dash Mounted |
| COLLISION MITIGATION SYSTEM {Bendix Wingman Fusion} Adaptive Cruise, Enhanced Collision Mitigation Multilane Auto & Stat Vehicle Braking, Stat Obj Alert, Roadway Depart Alert & Braking, Lane Depart Warning Switch & Spkrs, Ovrspd Alert & Action, Frt Radar & Camera, Drvr Display, Safety Direct Capable, Less Safety Direct Cable |
| |

| <u>Code</u> 8TXY | Description COLLISION MITIGATION MODIFIED {Bendix Wingman Fusion} Enhanced Stationary Vehicle Alert, Less Stationary Object Alert |
|---------------------|--|
| 8XJH | FOG LIGHTS (2) Clear Lens, LED, Rectangular, with White Light Source |
| 8WXB | HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position |
| 8XPA | HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled |
| 8WRB | HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On |
| 8WZL | HEADLIGHTS, WIG WAG with Bus Pupil Warning Lights |
| 8540 | HORN, ELECTRIC (2) Trumpet Style |
| 8WWJ | INDICATOR, LOW COOLANT LEVEL with Audible Alarm |
| 8RRE | RADIO PA Only, Includes Microphone, Less Outside Horn or Speakers |
| 8XKL | STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start |
| 8XJE | TURN SIGNALS, FRONT Dual Face, LED, Amber/Amber, Mounted on Top of Fender, Used with Standard Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors |
| FRONT END | |
| 9WBW | FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes |
| 9HCY | GRILLE Molded in Black, with Chrome Surround |
| 9WAB | HOOD TILT ASSIST {EASY TILT} Mechanical |
| 9AAB | LOGOS EXTERIOR Model Badges |
| 9AAE | LOGOS EXTERIOR, ENGINE Badges |
| SPEEDOMETER, TOOLS | S, MISC |
| 10020 | CHASSIS PAINT Full Chassis |
| 10AGB | COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360 |
| 10WUE | MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension |
| 10060 | PAINT SCHEMATIC, PT-1 Single Color, Design 100 |
| | Includes : PAINT SCHEMATIC ID LETTERS "NB" |
| 10788 | PAINT TYPE Urethane, One or Two Colors, Other than Imron or International. |
| 10XAK | PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500 |

PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500 Series Transmission on School and Commercial Buses (Supplied directly through Allison)

FUEL TANKS

| 15SLL | FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, Mounted Between Frame Rails and Behind Rear Axle |
|-------|--|
| 15WEP | DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow |
| 15LMR | FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor |
| 15LRE | LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle |

| <u>Code</u> WHEELS, TIRES - FRON | Description T |
|-------------------------------------|---|
| 27DUW | WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs |
| 7482133269 | (2) TIRE, FRONT 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position |
| WHEELS, TIRES - REAF | R |
| 28DUW | WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs |
| 7482133269 | (4) TIRE, REAR 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position |
| BODY FEATURES | |
| 47BDE | BUMPER, REAR Naviflex HD, 12" High, 3/16" Thick |
| 47BAR | SUPPORTS, REAR BUMPER Bolted to Frame |
| 47AYB | BODY, REAR Includes Emergency Door |
| 47ARH | BOWS, ROOF 14 ga., One Piece Construction |
| | Includes : BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail |
| 47BLU | FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Body Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arms |
| 47APX | FASTENERS, HEADLINER Screws |
| 47AZL | FLOOR, BODY with Wheel Wells |
| 47PHT | HANDLE, ASSIST Windshield Side Mounted, Left and Right, Stainless Steel |
| 47APR | HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation Full Length |
| 47ARP | LIGHT BARS Plastic |
| 47BBH | LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated |
| 47AXT | RUB RAILS, BODY (4) Conventional; Steel, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths, Includes Snow Rail |
| | Includes : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices |
| 47BBZ | SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor |
| 47AZE | SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths |
| 47ATB | SKIRT, BODY Conventional, 20", 16ga., 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths |
| | Includes : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets |
| 47BLD | STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish |
| 47AUR | TIE DOWNS, BODY Grade 8 Bolts, Every Body Section |
| | Includes : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning |

| <u>Code</u> 47DAJ | Description COVER, REAR DOOR INSIDE HANDLE Partial Coverage |
|----------------------|---|
| 47PCW | DOOR, ENTRANCE, FRONT Electric, Outward Opening, with Single Pane Glass |
| 47DAK | FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body |
| 47DDE | HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance |
| 47DEY | HANDLE, EXTERIOR, REAR Emergency Door; Yellow |
| 47DDH | HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover |
| 47AVK | INTERLOCK, STARTER with Key Switch for Entrance with Lock |
| 47DDU | LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke |
| 47EYL | LOCK, ENTRANCE DOOR in External Release, with Key |
| 47DEK | LOCK, REAR DOOR with Ignition Starter Interlock |
| 47BDJ | COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) USB-C Port |
| 47EYH | COMPARTMENT, TOOLBOX, RT BPR 13" x 15" x 25.5", with Lock |
| 47EBM | HOLD DOWN, BATTERY For Up To 3 Batteries |
| 47BMA | WASTE CONTAINER Removable, Located in Driver Area |
| 47LAU | INSULATION, ROOF/SIDES/BULKHEAD 1.5" |
| 47LAT | NOISE REDUCTION, ROOF BOW Conventional; Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths |
| 47MBA | UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec |
| | Includes : UNDERCOATING Performed Before and After Mounting on Chassis |
| 47SPB | ALPHA/NUMERIC DECAL GUIDE Quantity 021-30 |
| 47MNT | ARROW, RR DOOR, INSIDE Decal; Red, .75" Stroke, Indicating Handle Direction |
| 47MNV | ARROW, RR DOOR, OUTSIDE Decal; Black .75" Stroke, Indicating Handle Direction |
| 47AJA | BODY CERTIFICATION TAG Metal |
| 47APJ | BODY RATING TAG Metal; for State of Texas, Includes Design Capacity and Seat Capacity |
| 47AJC | BODY TAG, METAL Capacity to Include the Total Number of Passengers |
| 47PLX | LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door |
| 47MJR | LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside |
| 47NGP | LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door |
| 47MVA | LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield |
| 47MRU | LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside |
| 47NHL | LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside |
| 47MAV | LETTERS, SCHOOL BUS SIDE Decal; "SCHOOL BUS"; in 8" Reflective Black Letters, Each Side |
| 47MZB | LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and Rear Cap |
| 47MVC | LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser |

| <u>Code</u> 47NTE | Description LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door Over Driver Window and Entrance Door |
|----------------------|---|
| 47NMG | OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door |
| 47NKR | PAINT COLOR, BODY INTERIOR Light Gray |
| 47NJA | PAINT COLOR, BODY EXTERIOR 4421 School Bus Yellow |
| 47NJM | PAINT FLASHER BACKGRD 0001 Canyon Black |
| 47NTY | PAINT HOOD AND FENDER To Match Body Exterior |
| 47NKD | PAINT COLOR, ROOF 9219 Winter White, Beginning 5" Above Drip |
| 47NKL | PAINT, RUB RAIL Flange to Flange |
| 47NAB | PAINT COLOR, RUB RAILS 0001 Canyon Black |
| 47NGJ | PAINT, WINDOW BOW CAPS 0001 Canyon Black, Side Only |
| 47NGW | SEAL, RUB RAILS Top Edge, All Rails |
| 47MRN | STRIPING, E/E WINDOW, LEFT (02) Perimeter, 1" Yellow |
| 47MUP | STRIPING, E/E WINDOW, RIGHT (02) Perimeter, 1" Yellow |
| 47MSA | STRIPING, PERIMETER, REAR Emergency Door, 1" Yellow Reflective |
| 47MVM | STRIPING, REAR END 1" Yellow |
| 47MSJ | STRIPING, ROOF HATCH, FRONT Decal, Perimeter, 1" Yellow |
| 47MSK | STRIPING, ROOF HATCH, REAR Decal, Perimeter, 1" Yellow |
| 47MSS | STRIPING, SEATLINE 2" Yellow |
| 47MTY | WIRING DIAGRAM Schematic, Electrical |
| | Includes : ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver Window |
| 47SBB | SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths |
| 47BDA | FLOOR, COATING, Chemguard Metal Coating, Applied to Main Floor and Intermediate Sills |
| 47KEJ | DISARM, POST TRIP INSPECTION Button Located on Light Bar at Rear of Bus |
| 47KEB | MONITOR, POST TRIP INSPECTION {Leave No Student Behind} Accessory Controlled, with Push Button Alarm Disable at Rear of Bus Prompts Driver to Walk to Back of Bus to Disable Alarm |
| 47DNN | SWITCH, LOCATION Left of Driver; Includes Master Flasher, Amber Flasher, and 2 Position Door Control |
| BODY FEATURES | |
| 48ANT | WINDOW, DRIVER Laminated, Clear |
| 48BJL | COLOR, WINDOW FRAME, PASS (26) Passenger Window, Black |
| 48BAH | WINDOW, E/E, LEFT (2) Vertical Hinge |
| 48BKP | WINDOW, E/E, RIGHT (2) Vertical Hinge |
| 48AUN | WINDOW PASSENGER TINT Conventional: 28% Light Laminated Glass 78" Headroom with 31'2" 31'11" |

| Code | Description |
|-------|--|
| 48ARU | WINDOW, SASH (20) 27" Sections, 9"x 23" Opening |
| 48ASP | WINDOW, SASH +9 SECTIONS (2) 9" x 32 1/4" Opening |
| 48APL | WINDOW, STOPS 12" Opening, Only with 78" Headroom |
| 48PAY | AISLE POSITION Center, for balanced seating |
| 48PBB | FLOOR COVERING, COLOR Black |
| 48PUP | FLOOR COVERING, TRIM Omit |
| 48UWV | FLOOR COVERING, TYPE Koroseal, One Piece, Vinyl, All Body Lengths, Black |
| 48VVR | STEP TREADS {Koroseal} Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded Steps |
| 48PAV | WHEEL POCKET COVER Plastic, ABS |
| 48HDJ | AIR CONDITIONER, BODY IC Air, 120,000 BTU, Evaporators FM55 Front & Rear Flush Mounted & TA93 Side Mounted, Condensers SMC3L Skirt Mounted, Compressors TM21, #16 Suction Hose, EC4.0 Control System |
| 48PKC | HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System |
| 48PKR | FAN, DEFOG LEFT CENTER 6.50" Diameter, Black, Mounted Left of Center Post, 2-Speed Switch in Panel |
| 48PPP | HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Driver Area |
| 48PMJ | HEATER, PASS, LT REAR 84,500 BTU |
| | Includes : AIR FILTER |
| 48PNW | HEATER, WATER PUMP {2 MPU 12} Self Priming, with Plastic Housing |
| 48UZN | ROOF HATCH, FRONT {Specialty Hybrid Adv H1975-025-191-0F} Emergency Exit with Outside Release, Alarm, English Decals |
| 48UZT | ROOF HATCH, REAR {Specialty Hybrid Adv H1975-025-191-0F} Emergency Exit with Outside Release, Alarm, English Decals |
| 48PPS | ROOF VENT, FRONT Static |
| 48PRH | ROOF VENT, REAR Static |
| 48PPC | SWITCH, HTR FAN, REAR, LT with 84,500 BTU Rear Heater Only |
| 48UXS | ARM REST, DRIVER Right |
| 48VUK | SEAT, DRIVER {National ABTS 2000} Air Suspension Dual Shock, High Back with Integral Headrest, Isolated, with 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Adjustable Lumbar Support, Includes Additional Padding, 3 Point Lap and Shoulder Belts |
| | Includes : SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor |
| 48PXP | UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz. |
| 48PVK | UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Brown |
| 48PVA | UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert |
| 48PWR | UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz. |
| 48BDS | BARRIER, CRASH, AFT ENTRY DOOR 39", 2 Leg |
| 48RAL | BARRIER, CRASH, AFT DRIVER 39", 1 Leg |
| | |

| <u>Code</u> 48UZX | <u>Description</u> HAND RAIL, ENTRANCE DOOR, AFT Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, Lower Rail 1" OD |
|----------------------|--|
| 48UZY | HAND RAIL, ENTRANCE DOOR, FWD Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, Lower Rail 1" OD |
| 48RET | PANEL, MODESTY, AFT ENTR DOOR Mounted Under Barrier |
| 48REP | PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier |
| 48ACN | SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing |
| 48USV | SEAT BACK, PASSENGER High Back |
| 48XGC | SEAT,26",WALL,3PT,LT {BTI Seating System} (01) High Back, with 3 Point Seat Belts |
| 48YAH | SEAT,39",WALL,3PT,LT {BTI Seating System} (12) High Back, with 3 Point Seat Belts |
| 48YAX | SEAT,39",WALL,3PT,RT {BTI Seating System} (13) High Back, with 3 Point Seat Belts |
| 48PWA | UPHOLSTERY, PASS SEATS, COLOR Brown, for Seats, Barriers and Head Bumpers |
| 48PHR | UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (25-26) Seats |
| 48RLX | CUSHION, SEAT 15" Depth |
| 48RRA | UPHOLSTERY, SEAT, STITCHING Single |
| BODY FEATURES | |
| 48HAC | WINDOW, ENTRANCE DOOR Laminated, Clear, with Single Piece Glass |
| 49AMJ | ALARM, BACKING {Ecco #575} 107 dB |
| 49AMT | CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses |
| 49BCN | FLASHER SYSTEM (8) Warning Lights, 8-Lamp System, Electronic Relay Flasher, Non-Sequential Operation, Red Lights Activate with Door Open |
| 49DBR | HOOD, WARNING LAMP (4) Black, 8-Lamp System, One Hood Above Two Lights |
| 49JBU | LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light |
| 49BCR | LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection |
| 49ATV | LIGHT, INDIC, WARNING LIGHTS Red and Amber |
| | Includes : LIGHTS, WARNING Indicator Located in Instrument Cluster |
| 49JBV | LIGHT, LICENSE PLATE {Sound Off/OptiLuxx} LED, with Mounting Gasket |
| 49JBW | LIGHT, STEP {Sound Off/OptiLuxx} 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door |
| 49EYH | LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High |
| 49ZNC | LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange |
| 49NGD | LIGHTS, BACK UP, ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Oval LED Mounted on Left and Right Skirts, Aft of Rear Wheel Pocket Area, Below Seat Line Rub Rail, Illumination at Rear Tire, Wired to Reverse Light Signal |
| 49JBS | LIGHTS, CLUSTER {Sound Off/OptiLuxx} Oval, 4 Internal LEDs per Light; Amber Front and Red Rear |
| 49BYZ | LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber |

| <u>Code</u> 49EAX | Description LIGHTS, DIRECTIONAL, SIDE (4) {Sound Off/OptiLuxx} Rectangular LED Armored, 2 Each Side First Section Aft Entrance Door & Forward Rear Wheel Pocket |
|----------------------|---|
| 49JER | LIGHTS, DOME LED, Rectangular Recessed Type, Stagger Mounted, for 34'02", 34'11", 35'08" Body Lengths |
| 49ESC | LIGHTS, DOME, DRIVER (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch |
| 49JED | LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear |
| 49ZNN | LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units 30 Foot or Longer |
| 49BYT | LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red |
| 49ZNG | LIGHTS, STOP & TAIL ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Round LED, Red, with Flange |
| 49NGJ | LIGHTS, WARNING (8) {Sound Off/OptiLuxx} (4) 7" Round Red Strobing LED and (4) 7" Round Amber Strobing LED, 2 Front, 2 Rear Each Color |
| 49CME | MONITOR, LIGHT SYSTEM with 16 LED or Incandescent Indicator Lights |
| 49AWV | SPEAKERS AND WIRING (8) Flush Mounted In Light Bar |
| 49EKR | STOP ARM, FRONT Electric, Metal Blade, 18" Octagon, Double Sided, 1/2" White Border, Engineering Grade, Flashing Red Incandescent Lights |
| 49EKV | STOP ARM, LEFT REAR Electric, Metal Blade, 18" Octagon, Single Sided, 1/2" White Border, Engineering Grade, Flashing Red Incandescent Lights |
| 49SAA | SWITCH, INSTRUMENT PANEL LIGHTS; Rheostat |
| 49AAZ | SWITCH, INTERRUPT CROSS GATE Single Cycle; with Auto Reset, Located In Driver Compartment |
| 49EVL | SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP ", for Separate Solenoid, with Red Switch in Panel |
| 49AMY | SWITCH, REAR DOOR BUZZER for Emergency Door |
| 49BXN | SWITCH, RED, OVERRIDE WARNING Wired Hot, with ESC, Mounted Left of Driver |
| 49EGN | MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco Mini Hawk-Eye} Heated, Stainless Steel |
| | Includes : MIRROR MOUNT Attached to Body with Metal Backing Plates |
| 49EGB | MIRROR, INSIDE 10" x 30", Clear |
| 49EXN | MIRROR, REAR VIEW, EXTERIOR {Rosco Open-View} Stainless Steel, Motorized Head, Heated, Detent Breakaway Brackets |
| 49ENL | VISOR, INTERIOR, LEFT FRONT 10" x 30", For Left Windshield |
| 49GDS | COMPARTMENT ABOVE DRIVER Left of the Driver |
| | <u>Includes</u> : COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type |
| 49JGJ | FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle |
| 49JGN | FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat |
| 49GAY | KIT, BODY FLUID Texas |
| 49EBA | KIT, FIRST AID Plastic; 24 Unit, Spec State |
| 49MZV | LATCH, COMPARTMENT Locking, for Overhead Storage Compartment |
| | |

| <u>Code</u> 49JGT | Description LOCATION, BODY FLUID KIT on Driver Overhead Compartment |
|----------------------|---|
| 49GCH | LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws |
| 49GDG | PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light |
| 49GLP | REFLECTORS, REAR (2) 3", Red, Mounted with Screws |
| 49GLM | REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted with Screws |
| 49GLA | REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third Rub Rail From the Top |
| 49GLG | REFLECTORS, SIDE, REAR (2) 3", Red, Mounted with Screws |
| 49GES | SAFETY TRIANGLES Warning Reflectors, Located in Tool Box, Includes Decals |
| 49GUB | CUTTER, SEAT BELT {TIE TECH Safecut} for Cutting Seat Belts |
| 49JGE | CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver |
| 49JAC | DEF FILLER DOOR with Non-Locking Latch |
| 49GUK | FENDERS, RUBBER, REAR (2) |
| 49MZS | FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position |
| 49CKT | FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only |
| 49GUM | INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel |
| 49GUY | MUD FLAPS, REAR WHEELS (2) Anti-Spray, Anti-Sail |
| 49ESH | SIGN, DESTINATION, FRONT LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS" |
| 49ESG | SIGN, DESTINATION, REAR LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS" |
| 49UBZ | STATE OF OPERATION Texas |
| OBD004 | MISCELLANEOUS LIGHTED DESTINATION SIGNS 49ESG & 49ESH TO BE ACTIVATED BY IGNITION |
| | Services Section: |
| WARRANTY | |
| 40126 | WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later, CTS-3304H |
| 40YET | SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident |
| 40YGR | SRV CONTRACT, EXT VEH COVERAGE {Navistar} To 60-Month/100,000 Miles (160,000 km), Covers 100% Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or Corrosion of Cab/Cowl Structure and Paint |
| BODY FEATURES | |
| 49GVN | WARRANTY 5-Year, Limited |
| | DOT INSPECTION - WW SALES |
| | |

SET GOVERNOR SPEED 65 MPH

Description WEIGHT SLIP

<u>Code</u>

EYE MAX LED HAWKEYE XVIEW STAINLESS STEEL MIRROR - LHB

PRE DELIVERY INSPECTION CE MODEL

FIRST LIGHT ELECTRIC OPERATED FRONT AND REAR LED STOP ARM - LHB INSTALL

Financial Summary 2025 CE SCHOOL BUS (PB110)

(US DOLLAR)

Description

Net Sales Price:

Price

\$320,064.00

Prices are good for 30 days from the date of this proposal.

PRICE PER BUS: \$160,032.00

PRICE FOR (2) TWO BUSES: \$320,064.00

This quote would be produced as a 2025MY product if awarded. Feature codes are subject to update upon IC Bus completion of code references. Estimated delivery: 300-365 Days from receipt of a purchase order. Longhorn Bus Sales will not be held responsible for material shortages or delays due to the global COVID-19 pandemic or any other reasons outside of our control, that of the represented OEM (IC Corp) or third-party vendors used to complete a customers' bus order. Any buses ordered, will be subject to any and all applicable surcharges at the time of build, due to the volatility of the producers material costs. Any applicable surcharges will be the responsibility of the buyer. A bus order may be delivered without OEM or third-party products (i.e., A/C, GPS, two-way radios, camera surveillance equipment, etc.), and any such items will be installed immediately upon availability. These shortages/delays will not hold up invoicing and or payment. Instructions for payment of invoices will be provided upon invoicing. No one from Longhorn Bus Sales will ever contact or email wiring or ACH instructions for payment. Due to industry constraints, quote pricing may fluctuate.

Price does not include Buy Board fee of \$800 per purchase order, please add if applicable. Buy Board contract 722-23.

40YGC Warranty: Longhorn Bus Sales will cover the warranty for 24-months/unlimited mileage. (Navistar will cover the first 50K miles. Longhorn Bus will cover 50K+ miles, up to the ending of the 24-month period, as per current Texas School Bus Specifications.

CODE "49GVN WARRANTY 5-YEAR, LIMITED" IS A NAVISTAR WARRANTY ONLY, IT DOES NOT APPLY TO ANY AFTERMARKET PARTS

By signing this document in acceptance of an order, the customer acknowledges that all equipment listed within this document is correct. Longhorn Bus Sales will not be responsible for any miss-built units. Any changes to what is listed herein, may result in additional charges to the order. Thank you.

Approved by Seller:

Official Title and Date

Firm or Business Name

Accepted by Purchaser:

Authorized Signature

Authorized Signature and Date

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.