

The Tennis Court Company

P.O Box 2929

Denton, Texas 76202

Office: 940-271-1393

Fax: 940-239-0140

PROPOSAL

PROPOSAL SUBMITTED TO:

ddaniel@aledo.k12.tx.us

JOB: Aledo High School

Refurbish 6 tennis courts
And windscreens

DATE: July 6, 2010

REFURBISHING OF SIX CONCRETE TENNIS COURTS: We propose to furnish all material, engineering, labor and insurance to perform the following work items for the amount shown.

COURT SURFACING: Grind courts with concrete surface grinder, clean out all cracks, pressure wash clean, let dry. Fill all lows 1/8" or more with concrete patch mix. Apply one coat of Plexipave acrylic resurfacer with 60-80 mesh sand over all patched areas; apply one coat over all courts. Apply minimum two coats of Plexipave acrylic color over all with 120 mesh sand. Stripe with textured white line paint to U.S.T.A. standards. Repaint existing net posts. Color to be Florida Green.

Complete for the sum of.....**Total \$ 29,880.00**

WINDSCREENS: Remove old windscreens. Install M.Putterman 9' Tenn-air windscreens with 12"x12" bound air vents every 10' apart, approximately 600 lf complete for the sum of.....**Total \$ 4,790.00**

ACCEPTANCE OF PROPOSAL

The above specifications and conditions are satisfactory and are accepted. The TCC is authorized to do the work as specified. Payment will follow the above schedule. All material is guaranteed to be as specified. All work and construction clean up to be completed in a workmanship like manner according to standard practice. Any alteration or deviation from specifications above involving extra costs will be executed only upon written orders, and will become an extra charge over and above the estimate.

WARRANTY: The Tennis Court Company cannot be responsible for cracks/spalled concrete reappearing in concrete/ asphalt base do to sub-base movement, or to moisture in sub-base or to water standing on courts due to improper construction and drainage. The procedures outlined above have been proven to be effective when applying color coatings to concrete/ asphalt pavements. However, coating bubbles and or blisters may occur due to the moisture content of concrete. The Tennis Court Company will guarantee for one year against material and workmanship.

NOTE: The success of all weather characteristics is dependant on a sound base with Good drainage and concrete meeting the requirements of the American Concrete Institute and The American Sports Builders Association. The Plexipave System will not prevent surface cracks from recurring.

Sincerely,

Richard C. Bartz

Member of the American Sports Builders Association