

CE SCHOOL BUS

Sales Proposal For:

Galveston ISD

Presented By:

LONGHORN BUS SALES

Prepared For: Galveston ISD Mike Praker 3101 83rd st.

Galveston, TX 77554-(409)740 - 1208

Reference ID: 5 77P DSL 3PT

Presented By: LONGHORN BUS SALES LINDA BLUME 9100 N LOOP E HOUSTON TX 77029 -(713)631-9306

Model Profile 2025 CE SCHOOL BUS (PB110)

AXLE CONFIG: 4X2

APPLICATION: School Transportation

MISSION: Requested GVWR: 31000. Calc. GVWR: 31000

Calc. Start / Grade Ability: 25.66% / 1.54% @ 55 MPH

Calc. Geared Speed: 79.2 MPH

DIMENSION: Wheelbase: 276.00, CA: N/A, Axle to Frame: 166.00

ENGINE, DIESEL: {Cummins B6.7 240} EPA 2021, 240HP @ 2400 RPM, 560 lb-ft Torque @ 1600 RPM, 2600 RPM

Governed Speed, 240 Peak HP (Max), School Bus Only

TRANSMISSION, AUTOMATIC: {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less

PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus

CLUTCH: Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING: {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity

AXLE, REAR, SINGLE: {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends Gear Ratio: 6.14

TIRE, FRONT: (2) 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position TIRE, REAR: (4) 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position

SUSPENSION, REAR, AIR, SINGLE: {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted

Outside the Rails

PAINT: Cab schematic 100NB

Location 1: 4421, School Bus Yellow (Std)

Chassis schematic N/A

<u>Code</u> PB11000	<u>Description</u> Base Chassis, Model CE SCHOOL BUS with 276.00 Wheelbase, N/A CA, and 166.00 Axle to Frame.	
BODY PLANS		
47AMG	BODY, BUS Conventional; 78" Headroom, 34'11" Body Length, +9 Section Rear, 78 Passenger, 276 WB	
	Includes : NOTE: Body Mandates Overall Vehicle Length of Greater than 40 Feet	
OBD001	BODY PLAN, NON-SPECIAL NEEDS USE 50ZCZ/49001	
49001	BODY PLAN, APPROVED VARIATION Number 001	
AXLE CONFIGURATION		
1ANA	AXLE CONFIGURATION {Navistar} 4x2	
ENGINE		
12ERS	ENGINE, DIESEL {Cummins B6.7 240} EPA 2021, 240HP @ 2400 RPM, 560 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max), School Bus Only	
12XCS	CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty	
12WZE	CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	
12VJG	EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2023	
12XCC	RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 Sqln Louvered, with 383 Sqln Charge Air Cooler, Includes In-Tank Oil Cooler	
	Includes : RADIATOR HOSES Premium, Rubber	
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On	
	Includes : FAN Nylon	
12VCE	AIR CLEANER Single Element, Fire Retardant Media	
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	
12VVN	CRUISE CONTROL Electronic	
12VYV	IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package	
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines	
12UGN	THROTTLE, HAND CONTROL Electronic	
TRANSMISSION		
13BBP	TRANSMISSION, AUTOMATIC {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus	
13WVW	NEUTRAL AT STOP OMIT	
13WYY	SHIFT CONTROL PARAMETERS (Allison) 1000 or 2000 Series Transmissions, Performance Programming	
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints	
13WEX	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series Transmission	

3

Code CLUTCH	<u>Description</u>	
11001	CLUTCH Omit Item (Clutch & Control)	
REAR AXLES, SUSPENS	SIONS	
14AKC	AXLE, REAR, SINGLE {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends . Gear Ratio: 6.14	
14TDV	SUSPENSION, REAR, AIR, SINGLE {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted Outside the Rails	
FRONT AXLES		
2ASH	AXLE, FRONT NON-DRIVING {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity	
FRONT SUSPENSIONS		
3ADB	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock Absorbers	
	Includes : SPRING PINS Rubber Bushings, Maintenance-Free	
CABS, COWLS, BODIES		
16010	COWL Flat Back	
16BAM	AIR CONDITIONER with Integral Heater and Defroster	
16VKB	CAB INTERIOR TRIM Classic, for Day Cab	
16GEG	GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	
	Includes : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped) : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)	
16HLJ	GAUGE, DEF FLUID LEVEL	
16HGH	GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission	
16563	HEATER SHUT-OFF VALVES (2) Ball Valve Type	
16XJP	INSTRUMENT PANEL Wing Panel	
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	
16VVJ	WINDSHIELD Three Piece, Bonded, with Shaded Band	
FRAMES		
1CAC	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL	
1LSH	BUMPER, FRONT Contoured, Steel, Naviflex Spray on Coating, Severe Duty	
1LMW	CROSSING GATE, FRONT Electric, Yellow Blade, Bumper Mounted	

4

Code	<u>Description</u> <u>Includes</u> : CONTROL ASSEMBLY Solid State, Located Rear of Front Bumper, Heater not Required : CROSSING GATE, FRONT Matches Contour of Bumper
1SAM	CROSSMEMBER, REAR, AF (2)
1WJE	WHEELBASE RANGE 276" (700cm) Only
BRAKES	
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4AZS	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
4GBL	BRAKE, PARKING {Bendix Intellipark} Electronic Park Brake, for Truck or Bus Applications
4XDD	BRAKES, FRONT {Meritor 15X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 5", 13,200-lb Capacity
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqln
4LAG	SLACK ADJUSTERS, FRONT {Gunite} Automatic
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqln Spring Brake
4LGG	SLACK ADJUSTERS, REAR {Gunite} Automatic
4SPA	AIR COMPRESSOR (Cummins) 18.7 CFM
4EDN	AIR DRYER (Bendix AD-9SI) with Heater, Includes Safety Valve
4VLE	AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side
4VLY	AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4WZT	GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121 Requirements, for Conventional Bus
4WJP	PARKING BRAKE INTERLOCK with Electronic Park Brake, Parking Brake Cannot be Released Until Ignition Switch is in "On" Position and Service Brake Pedal is Applied, Use with Air Brake Chassis Only
STEERING	
5PSA	STEERING GEAR {Sheppard M100} Power
5708	STEERING COLUMN Tilting
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
DRIVELINES	
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2

5

<u>Code</u> <u>Description</u>

6901 PROPSHAFT GUARD

EXHAUST SYSTEMS

7BMK EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long

Horizontal Tail Pipe

7SCP ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

7WCX HEAT SHIELD Between Exhaust & Fuel Tank, Mounted to AF Crossmember

7WBL TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper

ELECTRICAL SYSTEMS

8000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature

: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush

Mounted

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with

Turn Signal Lever

: WIRING, CHASSIS Color Coded and Continuously Numbered

8GXN ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote

Sense

8TTM BATTERY BOX Steel, with Powder Coat Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery

Capacity, Mounted Left Side Behind Front Axle Perpendicular to Frame Rail

8MJU BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud

8XDX BK WARN IND, PARK BK NOT SET Visual and Audible Alarm, Active Upon Ignition Off and Parking Brake Not

Set, Reminder to Set Parking Brake

8XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

8WKJ CLOCK Digital, White LED Lettering, Black Background, Black Bezel, 12 Hour Clock Format, Western Arial

Font Digital Readout, Display Dims by 50% When Headlights Are On, Dash Mounted

8TRG COLLISION MITIGATION SYSTEM (Bendix Wingman Fusion) Adaptive Cruise, Enhanced Collision Mitigation,

Multilane Auto & Stat Vehicle Braking, Stat Obj Alert, Roadway Depart Alert & Braking, Lane Depart Warning Switch & Spkrs, Ovrspd Alert & Action, Frt Radar & Camera, Drvr Display, Safety Direct Capable, Less Safety

Direct Cable

8TXY COLLISION MITIGATION MODIFIED (Bendix Wingman Fusion) Enhanced Stationary Vehicle Alert, Less

Stationary Object Alert

8XJH FOG LIGHTS (2) Clear Lens, LED, Rectangular, with White Light Source

8WXB HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

8XPA HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled

8WRB HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on

8WZL HEADLIGHTS, WIG WAG with Bus Pupil Warning Lights

<u>Code</u> <u>Description</u>

8540 HORN, ELECTRIC (2) Trumpet Style

8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

8RRE RADIO PA Only, Includes Microphone, Less Outside Horn or Speakers

8XKL STARTING MOTOR (Mitsubishi Electric Automotive America 90P47) 12-Volt, with Soft-Start

8XJE TURN SIGNALS, FRONT Dual Face, LED, Amber/Amber, Mounted on Top of Fender, Used with Standard

Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors

FRONT END

9WBW FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes

9HCY GRILLE Molded in Black, with Chrome Surround
9WAB HOOD TILT ASSIST {EASY TILT} Mechanical

9AAB LOGOS EXTERIOR Model Badges

9AAE LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

10020 CHASSIS PAINT Full Chassis

10AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data

Plan and International 360

10WUE MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension

10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "NB"

10788 PAINT TYPE Urethane, One or Two Colors, Other than Imron or International.

10XAK PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500

Series Transmission on School and Commercial Buses (Supplied directly through Allison)

FUEL TANKS

15SLL FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, Mounted Between

Frame Rails and Behind Rear Axle

15WEP DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow

15LMR FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor

15LRE LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

WHEELS, TIRES - FRONT

27DUW WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7482133269 (2) TIRE, FRONT 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position

WHEELS, TIRES - REAR

28DUW WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

Code

<u>Description</u>
(4) TIRE, REAR 11R22.5 Load Range H XZE2 (MICHELIN), 501 rev/mile, 75 MPH, All-Position 7482133269

BODY	FEAT	URES
------	------	------

BUMPER, REAR Naviflex HD, 12" High, 3/16" Thick SUPPORTS, REAR BUMPER Bolted to Frame BODY, REAR Includes Emergency Door
BODY DEAD Includes Emergency Dear
BODT, NEAR Includes Emergency Book
BOWS, ROOF 14 ga., One Piece Construction
Includes: BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail
FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Body Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arms
FASTENERS, HANDRAIL Plusnuts & Screws
FASTENERS, HEADLINER Screws
FLOOR, BODY with Wheel Wells
HANDLE, ASSIST Windshield Side Mounted, Left and Right, Stainless Steel
HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation Full Length
LIGHT BARS Plastic
LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated
RUB RAILS, BODY (4) Conventional; Steel, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths, Includes Snow Rail
Includes : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices
SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor
SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
SKIRT, BODY Conventional, 20", 16ga., 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
Includes : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets
STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish
TIE DOWNS, BODY Grade 8 Bolts, Every Body Section
Includes : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning
COVER, REAR DOOR INSIDE HANDLE Partial Coverage
DOOR, ENTRANCE, FRONT Electric, Outward Opening, with Single Pane Glass
FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body
HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance
HANDLE, EXTERIOR, REAR Emergency Door; Yellow
HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover

8

	,
<u>Code</u> 47AVK	<u>Description</u> INTERLOCK, STARTER with Key Switch for Entrance with Lock
47DDU	LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke
47EYL	LOCK, ENTRANCE DOOR in External Release, with Key
47DEK	LOCK, REAR DOOR with Ignition Starter Interlock
47BDJ	COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) USB-C Port
47EYH	COMPARTMENT, TOOLBOX, RT BPR 13" x 15" x 25.5", with Lock
47EBM	HOLD DOWN, BATTERY For (2) Standard Size Batteries
47BMA	WASTE CONTAINER Removable, Located in Driver Area
47LAU	INSULATION,ROOF/SIDES/BULKHEAD 1.5"
47LAT	NOISE REDUCTION, ROOF BOW Conventional; Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47MBA	UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec
	Includes : UNDERCOATING Performed Before and After Mounting on Chassis
47SPB	ALPHA/NUMERIC DECAL GUIDE Quantity 021-30
47MNT	ARROW, RR DOOR, INSIDE Decal; Red, .75" Stroke, Indicating Handle Direction
47MNV	ARROW, RR DOOR, OUTSIDE Decal; Black .75" Stroke, Indicating Handle Direction
47AJA	BODY CERTIFICATION TAG Metal
47APJ	BODY RATING TAG Metal; for State of Texas, Includes Design Capacity and Seat Capacity
47AJC	BODY TAG, METAL Capacity to Include the Total Number of Passengers
47PLX	LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door
47MJR	LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside
47NGP	LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door
47MVA	LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield
47MRU	LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside
47NHL	LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside
47MAV	LETTERS, SCHOOL BUS SIDE Decal; "SCHOOL BUS"; in 8" Reflective Black Letters, Each Side
47MZB	LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and Rear Cap
47MVC	LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser
47NTE	LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door Over Driver Window and Entrance Door
47NMG	OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door
47NJA	PAINT COLOR, BODY EXTERIOR 4421 School Bus Yellow
47NKR	PAINT COLOR, BODY INTERIOR Light Gray

PAINT COLOR, ROOF 9219 Winter White, Beginning 5" Above Drip

9

47NKD

CodeDescription47NABPAINT COLOR, RUB RAILS 0001 Canyon Black47NJMPAINT FLASHER BACKGRD 0001 Canyon Black47NTYPAINT HOOD AND FENDER To Match Body Exterior47NKLPAINT, RUB RAIL Flange to Flange47NGJPAINT, WINDOW BOW CAPS 0001 Canyon Black, Side Only47NGWSEAL, RUB RAILS Top Edge, All Rails

47MRN STRIPING, E/E WINDOW, LEFT (02) Perimeter, 1" Yellow
47MUP STRIPING, E/E WINDOW, RIGHT (02) Perimeter, 1" Yellow

47MSA STRIPING, PERIMETER, REAR Emergency Door, 1" Yellow Reflective

47MVM STRIPING, REAR END 1" Yellow

47MSJ STRIPING, ROOF HATCH, FRONT Decal, Perimeter, 1" Yellow
47MSK STRIPING, ROOF HATCH, REAR Decal, Perimeter, 1" Yellow

47MSS STRIPING, SEATLINE 2" Yellow

47MTY WIRING DIAGRAM Schematic, Electrical

Includes

: ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver

Window

47SBB SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2", 31'11",

32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths

47BDA FLOOR, COATING, Chemquard Metal Coating, Applied to Main Floor and Intermediate Sills

47KEJ DISARM, POST TRIP INSPECTION Button Located on Light Bar at Rear of Bus

47KEB MONITOR, POST TRIP INSPECTION (Leave No Student Behind) Accessory Controlled, with Push Button

Alarm Disable at Rear of Bus Prompts Driver to Walk to Back of Bus to Disable Alarm

47DNN SWITCH, LOCATION Left of Driver; Includes Master Flasher, Amber Flasher, and 2 Position Door Control

BODY FEATURES

48ANT WINDOW, DRIVER Laminated, Clear

48BJL COLOR, WINDOW FRAME, PASS (26) Passenger Window, Black

48BAH WINDOW, E/E, LEFT (2) Vertical Hinge 48BKP WINDOW, E/E, RIGHT (2) Vertical Hinge

48AUN WINDOW, PASSENGER, TINT Conventional; 28% Light, Laminated Glass, 78" Headroom, with 31'2", 31'11",

32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths

48ARU WINDOW, SASH (20) 27" Sections, 9"x 23" Opening

48ASP WINDOW, SASH +9 SECTIONS (2) 9" x 32 1/4" Opening

48APL WINDOW, STOPS 12" Opening, Only with 78" Headroom

48PAY AISLE POSITION Center, for balanced seating

48PBB FLOOR COVERING, COLOR Black
48PUP FLOOR COVERING, TRIM Omit

Code **Description** FLOOR COVERING, TYPE Koroseal, One Piece, Vinyl, All Body Lengths, Black 48UWV 48VVR STEP TREADS (Koroseal) Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded Steps 48PAV WHEEL POCKET COVER Plastic, ABS 48HDJ AIR CONDITIONER, BODY IC Air, 120,000 BTU, Evaporators FM55 Front & Rear Flush Mounted & TA93 Side Mounted, Condensers SMC3L Skirt Mounted, Compressors TM21, #16 Suction Hose, EC4.0 Control System 48PKC HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System FAN, DEFOG LEFT CENTER 6.50" Diameter, Black, Mounted Left of Center Post, 2-Speed Switch in Panel 48PKR 48PPP HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Driver Area 48PMJ HEATER, PASS, LT REAR 84,500 BTU Includes : AIR FILTER 48PNW HEATER, WATER PUMP {2 MPU 12} Self Priming, with Plastic Housing 48UZN ROOF HATCH, FRONT (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, Alarm, English Decals 48UZT ROOF HATCH, REAR (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, Alarm, English Decals ROOF VENT, FRONT Static 48PPS 48PRH ROOF VENT, REAR Static SWITCH, HTR FAN, REAR, LT with 84,500 BTU Rear Heater Only 48PPC 48UXS ARM REST, DRIVER Right 48VUK SEAT, DRIVER (National ABTS 2000) Air Suspension Dual Shock, High Back with Integral Headrest, Isolated, with 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Adjustable Lumbar Support, Includes Additional Padding, 3 Point Lap and Shoulder Belts Includes : SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor 48PXP UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz. 48PVK UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Brown 48PVA UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert 48PWR UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz. 48BDS BARRIER, CRASH, AFT ENTRY DOOR 39", 2 Leg 48RAL BARRIER, CRASH, AFT DRIVER 39", 1 Leg 48UZX HAND RAIL, ENTRANCE DOOR, AFT Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, Lower Rail 1" OD HAND RAIL, ENTRANCE DOOR, FWD Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, 48UZY

PANEL, MODESTY, AFT ENTR DOOR Mounted Under Barrier

PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier

SHIELD, COURTESY, AFT/DRIVER IGNORE, DO NOT NEED FEATURE

Lower Rail 1" OD

48RET

48REP

OBD002

	2020 02 0011002 000 (1 0110)
<u>Code</u> 48ACN	<u>Description</u> SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing
48USV	SEAT BACK, PASSENGER High Back
48XGC	SEAT,26",WALL,3PT,LT {BTI Seating System} (01) High Back, with 3 Point Seat Belts
48YAH	SEAT,39",WALL,3PT,LT {BTI Seating System} (12) High Back, with 3 Point Seat Belts
48YAX	SEAT,39",WALL,3PT,RT {BTI Seating System} (13) High Back, with 3 Point Seat Belts
48PWA	UPHOLSTERY, PASS SEATS, COLOR Brown, for Seats, Barriers and Head Bumpers
48PHR	UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (25-26) Seats
48RLX	CUSHION, SEAT 15" Depth
48RRA	UPHOLSTERY, SEAT, STITCHING Single
BODY FEATURES	
48HAC	WINDOW, ENTRANCE DOOR Laminated, Clear, with Single Piece Glass
49AMJ	ALARM, BACKING {Ecco #575} 107 dB
49AMT	CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses
49BCN	FLASHER SYSTEM (8) Warning Lights, 8-Lamp System, Electronic Relay Flasher, Non-Sequential Operation, Red Lights Activate with Door Open
49DBR	HOOD, WARNING LAMP (4) Black, 8-Lamp System, One Hood Above Two Lights
49JBU	LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light
49BCR	LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection
49ATV	LIGHT, INDIC, WARNING LIGHTS Red and Amber
	Includes : LIGHTS, WARNING Indicator Located in Instrument Cluster
49JBV	LIGHT, LICENSE PLATE (Sound Off/OptiLuxx) LED, with Mounting Gasket
49JBW	LIGHT, STEP {Sound Off/OptiLuxx} 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door
49EYH	LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High
49ZNC	LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange
49NGD	LIGHTS, BACK UP, ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Oval LED Mounted on Left and Right Skirts, Aft of Rear Wheel Pocket Area, Below Seat Line Rub Rail, Illumination at Rear Tire, Wired to Reverse Light Signal
49JBS	LIGHTS, CLUSTER (Sound Off/OptiLuxx) Oval, 4 Internal LEDs per Light; Amber Front and Red Rear
49BYZ	LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber
49EAX	LIGHTS, DIRECTIONAL, SIDE (4) {Sound Off/OptiLuxx} Rectangular LED Armored, 2 Each Side First Section Aft Entrance Door & Forward Rear Wheel Pocket
49JER	LIGHTS, DOME LED, Rectangular Recessed Type, Stagger Mounted, for 34'02", 34'11", 35'08" Body Lengths
49ESC	LIGHTS, DOME, DRIVER (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch
49JED	LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear
49ZNN	LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units

30 Foot or Longer

Code **Description** LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red 49BYT 49ZNG LIGHTS, STOP & TAIL ADDITIONAL (2) (Sound Off/OptiLuxx) 4" Round LED, Red, with Flange LIGHTS, WARNING (8) (Sound Off/OptiLuxx) (4) 7" Round Red Strobing LED and (4) 7" Round Amber Strobing 49NGJ LED, 2 Front, 2 Rear Each Color 49CME MONITOR, LIGHT SYSTEM with 16 LED or Incandescent Indicator Lights 49AWV SPEAKERS AND WIRING (8) Flush Mounted In Light Bar 49EMY STOP ARM, FRONT (First Light) Electric, Fully Illuminated Stop Arm, 20.6" Octagon, Double Sided, Strobing LED Lights 49ENB STOP ARM, LEFT REAR {First Light} Electric, Fully Illuminated Stop Arm, 20.6" Octagon, Single Sided, Strobing LED Lights 49SAA SWITCH, INSTRUMENT PANEL LIGHTS; Rheostat 49AAZ SWITCH, INTERRUPT CROSS GATE Single Cycle; with Auto Reset, Located In Driver Compartment 49EVL SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP", for Separate Solenoid, with Red Switch in Panel 49AMY SWITCH, REAR DOOR BUZZER for Emergency Door 49BXN SWITCH, RED, OVERRIDE WARNING Wired Hot, with ESC, Mounted Left of Driver 49EGL MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco Mini Hawk-Eye} Black <u>Includes</u> : MIRROR MOUNT Attached to Body with Metal Backing Plates 49EGB MIRROR, INSIDE 10" x 30", Clear **OBD003** MIRROR, REAR VIEW, EXTERIOR Rear view mirrors Rosco AccuStyle Stainless Steel, Motorized Head, HEATED, Breakaway Bracket 49ENL VISOR, INTERIOR, LEFT FRONT 10" x 30", For Left Windshield COMPARTMENT ABOVE DRIVER Left of the Driver 49GDS Includes : COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type 49JGJ FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle 49JGN FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat 49GAY KIT, BODY FLUID Texas 49EBA KIT, FIRST AID Plastic; 24 Unit, Spec State 49MZV LATCH, COMPARTMENT Locking, for Overhead Storage Compartment 49JEY LOCATION, BODY FLUID KIT on Bulkhead LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws 49GCH

49GDG

49GLP

49GLM

REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted

PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light

REFLECTORS, REAR (2) 3", Red, Mounted with Screws

with Screws

	2025 CE SCHOOL BUS (PB110)		
<u>Code</u> 49GLA	<u>Description</u> REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third Rub Rail From the Top		
49GLG	REFLECTORS, SIDE, REAR (2) 3", Red, Mounted with Screws		
49GES	SAFETY TRIANGLES Warning Reflectors, Located in Tool Box, Includes Decals		
49GUB	CUTTER, SEAT BELT {TIE TECH Safecut} for Cutting Seat Belts		
49JGE	CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver		
49JAC	DEF FILLER DOOR with Non-Locking Latch		
49GUK	FENDERS, RUBBER, REAR (2)		
49MZS	FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position		
49CKT	FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only		
49GUM	INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel		
49GUY	MUD FLAPS, REAR WHEELS (2) Anti-Spray, Anti-Sail		
49ESH	SIGN, DESTINATION, FRONT LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"		
49ESG	SIGN, DESTINATION, REAR LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"		
49UBZ	STATE OF OPERATION Texas		
	Services Section:		
WARRANTY			
40126	WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later, CTS-3304H		
40RAP	SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident		
40PLG	SRV CONTRACT, EXT VEH COVERAGE {Navistar} To 60-Month/100,000 Miles (160,000 km), Covers 100% Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or Corrosion of Cab/Cowl Structure and Paint		
BODY FEATURES			
49GVN	WARRANTY 5-Year, Limited		

49GVN WARRANTY 5-Year, Limited

DOT INSPECTION - WW SALES

PRE DELIVERY INSPECTION CE MODEL

SET GOVERNOR SPEED 65 MPH

WEIGHT SLIP

SAFETY VISION 6 CAM SYS, INSTALLED BY SAFETY VISION AT SCHOOL - LHB

EYE MAX LED HAWKEYE XVIEW MIRROR - LHB

Financial Summary 2025 CE SCHOOL BUS (PB110)

(US DOLLAR)

	(OO DOLLAN)	
<u>Description</u>		<u>Price</u>
Net Sales Price:		\$820,480.00
Prices are good for 30 days from the date of this	proposal.	
PRICE PER BUS: \$164,096.00		
PRICE FOR (5) FIVE BUSES: \$820,480.00		
This quote would be produced as a 2025MY proof code references. Estimated delivery: 300-365 I responsible for material shortages or delays due that of the represented OEM (IC Corp) or third-pabe subject to any and all applicable surcharges a applicable surcharges will be the responsibility of (i.e., A/C, GPS, two-way radios, camera surveilla availability. These shortages/delays will not hold fluctuate.	Days from receipt of a purchase order the global COVID-19 pandemic or the global covid-19 pandemic or the time of build, due to the volatility the buyer. A bus order may be delivated equipment, etc.), and any such its the buyer.	er. Longhorn Bus Sales will not be held any other reasons outside of our control, omers' bus order. Any buses ordered, will y of the producers material costs. Any ered without OEM or third-party products tems will be installed immediately upon
Price does not include Buy Board fee of \$800 per	purchase order, please add if applic	cable. Buy Board contract 630-20.
CODE "49GVN WARRANTY 5-YEAR, LIMITED" AFTERMARKET PARTS	S A NAVISTAR WARRANTY ONLY	, IT DOES NOT APPLY TO ANY
By signing this document in acceptance of an ord is correct. Longhorn Bus Sales will not be resport in additional charges to the order. Thank you.		
Approved by Seller:		Accepted by Purchaser:
Official Title and Date		Firm or Business Name
Authorized Signature		Authorized Signature and Date
This proposal is not binding upon the seller with Seller's Authorized Signature	hout	
		Official Title and Date
The TOPS FET calculation is an estimate for re and reporting/paying appropriate FET to the II		or retailer is responsible for calculating

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.