



CE SCHOOL BUS

Sales Proposal For:
Pineywoods Community Academy

Presented By:
LONGHORN BUS SALES

Prepared For:

Pineywoods Community Academy
Bruce Marchand
602 S Raguette St.
Lufkin, TX 75904-3936
(936)634 - 5515
Reference ID: 42P DSL FR3P

Presented By:

LONGHORN BUS SALES
CHERYL C BELL
5665 SE LOOP 410
SAN ANTONIO TX 782223903
713-631-9306

Model Profile

2026 CE SCHOOL BUS (PB110)

AXLE CONFIG:	4X2
APPLICATION:	Activity Trip
MISSION:	Requested GVWR: 33000. Calc. GVWR: 33000 Calc. Start / Grade Ability: 21.77% / 1.39% @ 55 MPH Calc. Geared Speed: 87.7 MPH
DIMENSION:	Wheelbase: 276.00, CA: N/A, Axle to Frame: 166.00
ENGINE, DIESEL:	{Cummins B6.7 240} EPA 2024, 240HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max), School Bus Only
TRANSMISSION, AUTOMATIC:	{Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity
AXLE, REAR, SINGLE:	{Dana Spicer 23060SH} Single Reduction, 23,000-lb Capacity, R Wheel Ends Gear Ratio: 5.57
TIRE, FRONT:	(2) 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position
SUSPENSION, REAR, AIR, SINGLE:	{International IROS} 23,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted Outside the Rails
PAINT:	Cab schematic 100NB Location 1: 9219, Winter White (Std) Chassis schematic N/A

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

Code	Description
PB11000	Base Chassis, Model CE SCHOOL BUS with 276.00 Wheelbase, N/A CA, and 166.00 Axle to Frame. Bus Body Plan, AABV0000LX Seat Capacity, 77

BODY PLANS

47AMG	BODY, BUS Conventional; 78" Headroom, 34'11" Body Length, +9 Section Rear, 81 Passenger, 276 WB <u>Includes</u> : NOTE: Body Mandates Overall Vehicle Length of Greater than 40 Feet
49UBZ	STATE OF OPERATION Texas
51ZZZ	BODY PLAN, NON-SPECIAL NEEDS for Bus Body Configurator, OMIT Body Plan
49000	BODY PLAN, APPROVED VARIATION None

AXLE CONFIGURATION

1ANA	AXLE CONFIGURATION 4x2
------	------------------------

ENGINE

12EYG	ENGINE, DIESEL {Cummins B6.7 240} EPA 2024, 240HP @ 2400 RPM, 600 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max), School Bus Only
12VKB	EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2025
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood
10UAV	VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA /OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle. <u>Notes</u> : CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.
12XCC	RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 SqIn Louvered, with 383 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler <u>Includes</u> : RADIATOR HOSES Premium, Rubber
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On <u>Includes</u> : FAN Nylon
12VCE	AIR CLEANER Single Element, Fire Retardant Media
12702	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection, Nitrite Free
12VVN	CRUISE CONTROL Electronic
12VYV	IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines
12UGN	THROTTLE, HAND CONTROL Electronic

TRANSMISSION

13BBP	TRANSMISSION, AUTOMATIC {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus
13VWW	NEUTRAL AT STOP OMIT
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints
13WEX	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series Transmission

CLUTCH

11001	CLUTCH Omit Item (Clutch & Control)
-------	-------------------------------------

REAR AXLES, SUSPENSIONS

14AKZ	AXLE, REAR, SINGLE {Dana Spicer 23060SH} Single Reduction, 23,000-lb Capacity, R Wheel Ends . Gear Ratio: 5.57
14TEB	SUSPENSION, REAR, AIR, SINGLE {International IROS} 23,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted Outside the Rails

FRONT AXLES

2ASH	AXLE, FRONT NON-DRIVING {Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity
------	---

FRONT SUSPENSIONS

3ADB	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock Absorbers <u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free
------	--

CABS, COWLS, BODIES

16010	COWL Flat Back
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16VKB	CAB INTERIOR TRIM Classic, for Day Cab
16XCW	CAB, INTERIOR TRIM, CLOSEOUT Under IP, Driver Side
16GEG	GAUGE CLUSTER Premium Level; English with English Electronic Speedometer <u>Includes</u> : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped) : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
16HLJ	GAUGE, DEF FLUID LEVEL
16HGH	GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission
16563	HEATER SHUT-OFF VALVES (2) Ball Valve Type
16XJP	INSTRUMENT PANEL Wing Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16VVJ	WINDSHIELD Three Piece, Bonded, with Shaded Band

FRAMES

1CAC	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL
1LSG	BUMPER, FRONT Contoured, Steel, Painted Gloss Black, Severe Duty <u>Notes</u> : Bumper Thickness is .25"
1LNT	CROSSING GATE, FRONT Omit Item
1SAL	CROSSMEMBER, REAR, AF (1)
1LEG	LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper
1WJE	WHEELBASE RANGE 276" (700cm) Only

BRAKES

4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications <u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4AZS	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
4GBL	BRAKE, PARKING {Bendix Intellipark} Electronic Park Brake, for Truck or Bus Applications
4XDC	BRAKES, FRONT {Meritor 15X4 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 4", 13,200-lb Capacity
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqiN
4LAA	SLACK ADJUSTERS, FRONT {Haldex} Automatic
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqiN Spring Brake
4LGA	SLACK ADJUSTERS, REAR {Haldex} Automatic
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM
4EDN	AIR DRYER {Bendix AD-9SI} with Heater, Includes Safety Valve
4VLE	AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
4VLY	AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4WZT	GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121 Requirements, for Conventional Bus
4WJP	PARKING BRAKE INTERLOCK with Electronic Park Brake, Parking Brake Cannot be Released Until Ignition Switch is in "On" Position and Service Brake Pedal is Applied, Use with Air Brake Chassis Only

STEERING

5PSA	STEERING GEAR {Sheppard M100} Power
5708	STEERING COLUMN Tilting
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black

DRIVELINES

6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2
6901	PROPSHAFT GUARD

EXHAUST SYSTEMS

7BMK	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long Horizontal Tail Pipe
7SCP	ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger
7WCX	HEAT SHIELD Between Exhaust & Fuel Tank, Mounted to AF Crossmember
7WBL	TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper

ELECTRICAL SYSTEMS

8000	<p>ELECTRICAL SYSTEM 12-Volt, Standard Equipment</p> <p><u>Includes</u></p> <ul style="list-style-type: none"> : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WIRING, CHASSIS Color Coded and Continuously Numbered
8GXN	ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote Sense
8RPP	ANTENNA Shark Fin, Roof Mounted
8TTK	BATTERY BOX Steel, with Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted Left Side Behind Front Axle Perpendicular to Frame Rail
8MSG	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
8XDX	BK WARN IND,PARK BK NOT SET Visual and Audible Alarm, Active Upon Ignition Off and Parking Brake Not Set, Reminder to Set Parking Brake
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8WKJ	CLOCK Digital, White LED Lettering, Black Background, Black Bezel, 12 Hour Clock Format, Western Arial Font Digital Readout, Display Dims by 50% When Headlights Are On, Dash Mounted
8TUT	COLLISION MITIGATION SYSTEM Omit
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position
8XPA	HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On
8540	HORN, ELECTRIC (2) Trumpet Style
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8RRC	RADIO AM/FM/USB Input/Auxiliary Input, Includes Wiring and Antenna, with Public Address System
8XKL	STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start
8XPN	USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel

FRONT END

9WBW	FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes
9HCY	GRILLE Molded in Black, with Chrome Surround
9WAB	HOOD TILT ASSIST {EASY TILT} Mechanical
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

10020	CHASSIS PAINT Full Chassis
10AGB	COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360
10WUE	MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension
10WTU	MULTI FUNCTIONAL BUS ID To be Used for Multi Functional School Activity Bus, Non Route Use Only, Letter of Compliance from End User is Required
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100 <u>Includes</u> : PAINT SCHEMATIC ID LETTERS "NB"
10788	PAINT TYPE Urethane, One or Two Colors, Other than Imron or International.
10XAK	PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500 Series Transmission on School and Commercial Buses (Supplied directly through Allison)
10AHZ	ENTRANCE DR COVERAGE CREDIT Bus Entrance Door Service Contract Coverage Credit

FUEL TANKS

15SLL	FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, Mounted Between Frame Rails and Behind Rear Axle
-------	---

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

Code	Description
15WEP	DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow
15LMN	FUEL/WATER SEPARATOR {Racor 400 Series,} 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor
15LRE	LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

WHEELS, TIRES - FRONT

27DWT	WHEELS, FRONT {Accuride 43644} DISC; 22.5x8.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7382135809	(2) TIRE, FRONT 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position

WHEELS, TIRES - REAR

28DWT	WHEELS, REAR {Accuride 43644} DUAL DISC; 22.5x8.25 Rims, Extra Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7382135809	(4) TIRE, REAR 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position

BODY FEATURES

47BAK	BUMPER, REAR Painted, 12" High, 3/16" Thick
47BAR	SUPPORTS, REAR BUMPER Bolted to Frame
47AYB	BODY, REAR Includes Emergency Door
47ARH	BOWS, ROOF 14 ga., One Piece Construction
	<u>Includes</u> : BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail
47BLU	FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Body Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arms
47APX	FASTENERS, HEADLINER Screws
47AZL	FLOOR, BODY with Wheel Wells
47PBZ	HANDLE, ASSIST Windshield Side Mounted, Left and Right, Body Color
47APR	HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation Full Length
47ARP	LIGHT BARS Plastic
47BBH	LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated
47MBN	ROOF CAPS Smooth Front & Rear, for Commercial Bus & Activity Bus
47AVH	RUB RAILS, BODY (3) 16ga., Steel
	<u>Includes</u> : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices
47BBZ	SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor
47AZE	SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47ASG	SKIRT, BODY for Conventional, 14 1/2", 16ga
	<u>Includes</u> : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
47BLD	STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish
47AUR	TIE DOWNS, BODY Grade 8 Bolts, Every Body Section
	<u>Includes</u> : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning
47DAJ	COVER, REAR DOOR INSIDE HANDLE Partial Coverage
47DYL	DOOR, ENTRANCE, FRONT Air, Outward Opening, with Single Pane Glass
47DAK	FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body
47DDE	HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance
47NLS	HANDLE, EXTERIOR, REAR Emergency Door; White
47DDH	HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover
47DDU	LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke
47EYL	LOCK, ENTRANCE DOOR in External Release, with Key
47DEK	LOCK, REAR DOOR with Ignition Starter Interlock
47BDJ	COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) USB-C Port
47EVY	COMPARTMENT, LUGGAGE, LT MID 114" x 24" x 22"
	<u>Includes</u> : HINGES Rubber : LATCH, T-HANDLE, LOCKING Stainless Steel
47EWA	COMPARTMENT, LUGGAGE, RT MID 114" X 24" X 22"
47EBM	HOLD DOWN, BATTERY For Up To 3 Batteries
47EBD	LOCK, BATTERY COMPARTMENT Standard Location
47EMV	LUGGAGE RACK, INTERIOR Tubular, Below Light Bar, 22 Bow
47BMA	WASTE CONTAINER Removable, Located in Driver Area
47LAU	INSULATION, ROOF/SIDES/BULKHEAD 1.5"
47LAT	NOISE REDUCTION, ROOF BOW Conventional; Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47MBA	UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec
	<u>Includes</u> : UNDERCOATING Performed Before and After Mounting on Chassis
47AJB	BODY CERTIFICATION TAG Mylar Label
47AJC	BODY TAG, METAL Capacity to Include the Total Number of Passengers
47PLX	LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door
47MJR	LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside
47NGP	LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door
47MVA	LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield
47MRU	LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside
47NHL	LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
47MZB	LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and Rear Cap
47MVC	LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser
47NTE	LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door Over Driver Window and Entrance Door
47NMG	OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door
47NKM	PAINT COLOR, BODY INTERIOR 9384 Spring White
47NJB	PAINT COLOR, BODY EXTERIOR 9219 Winter White
47NJS	PAINT COLOR, BUMPER Rear, 0001 Canyon Black
47NXU	PAINT FLASHER BACKGRD To Match Body Color
47NGR	PAINT HOOD AND FENDER 9219 Winter White
47NKL	PAINT, RUB RAIL Flange to Flange
47NAA	PAINT COLOR, RUB RAILS 9219 Winter White
47NGJ	PAINT, WINDOW BOW CAPS 0001 Canyon Black, Side Only
47NGW	SEAL, RUB RAILS Top Edge, All Rails
47MUR	STRIPING, E/E WINDOW, LEFT (02) Perimeter, 1" White
47MXB	STRIPING, E/E WINDOW, RIGHT (02) Perimeter, 1" White
47MSC	STRIPING, PERIMETER, REAR Emergency Door, 1" White Reflective
47KBN	STRIPING, ROOF HATCH, FRONT {3M} Decal, Perimeter, 1" White Fluorescent Diamond Grade
47KBP	STRIPING, ROOF HATCH, REAR {3M} Decal, Perimeter, 1" White Fluorescent Diamond Grade
47MTY	WIRING DIAGRAM Schematic, Electrical
	<u>Includes</u> : ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver Window
47SBS	SUB FLOOR, PLYWOOD Conventional; B-C Exterior Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47MZA	MONITOR, POST TRIP INSPECTION Omit
47DRN	SWITCH, LOCATION Left of Driver; Includes 2 Position Door Control

BODY FEATURES

48ANT	WINDOW, DRIVER Laminated, Clear
48BJL	COLOR, WINDOW FRAME, PASS (26) Passenger Window, Black
48BAH	WINDOW, E/E, LEFT (2) Vertical Hinge
48BKP	WINDOW, E/E, RIGHT (2) Vertical Hinge
48AUN	WINDOW, PASSENGER, TINT Conventional; 28% Light, Laminated Glass, 78" Headroom, with 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
48ARU	WINDOW, SASH (20) 27" Sections, 9"x 23" Opening
48ASP	WINDOW, SASH +9 SECTIONS (2) 9" x 32 1/4" Opening

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
48APL	WINDOW, STOPS 12" Opening, Only with 78" Headroom
48PAY	aisle POSITION Center, for balanced seating
48PBB	FLOOR COVERING, COLOR Black
48PJR	FLOOR COVERING, TRIM Aluminum
48PJZ	FLOOR COVERING, TYPE {Koroseal} All Body Lengths
48VVR	STEP TREADS {Koroseal} Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded Steps
48PAV	WHEEL POCKET COVER Plastic, ABS
48PKC	HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System
48UZK	FAN, DEFOG LEFT OF DRIVER 6.50" Diameter, Black, Mounted on Driver Overhead Compartment, 2 Speed Switch in Panel
48PMJ	HEATER, PASS, LT REAR 84,500 BTU Includes : AIR FILTER
48PNW	HEATER, WATER PUMP {2 MPU 12} Self Priming, with Plastic Housing
48UZN	ROOF HATCH, FRONT {Specialty Hybrid Adv H1975-025-191-0F} Emergency Exit with Outside Release, Alarm, English Decals
48UZT	ROOF HATCH, REAR {Specialty Hybrid Adv H1975-025-191-0F} Emergency Exit with Outside Release, Alarm, English Decals
48PPS	ROOF VENT, FRONT Static
48UXM	ARM REST, DRIVER Left and Right
48RYW	SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Isolated, with 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes Additional Back Padding Includes : SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor
48PXP	UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz.
48PVN	UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Gray
48PVA	UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert
48PWR	UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz.
48BDS	BARRIER, CRASH, AFT ENTRY DOOR 39", 2 Leg
48RAL	BARRIER, CRASH, AFT DRIVER 39", 1 Leg
48UZX	HAND RAIL, ENTRANCE DOOR, AFT Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, Lower Rail 1" OD
48UZY	HAND RAIL, ENTRANCE DOOR, FWD Dual Height Stainless Steel, Upper Rail 1.25" OD 28" Above Floor, Lower Rail 1" OD
48REP	PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier
48ACN	SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing
48USV	SEAT BACK, PASSENGER High Back

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
48XGC	SEAT,26",WALL,3PT,LT {BTI Seating System} (01) High Back, with 3 Point Seat Belts
48YAH	SEAT,39",WALL,3PT,LT {BTI Seating System} (12) High Back, with 3 Point Seat Belts
48YAX	SEAT,39",WALL,3PT,RT {BTI Seating System} (13) High Back, with 3 Point Seat Belts
48PWD	UPHOLSTERY, PASS SEATS, COLOR Gray, for Seats, Barriers and Head Bumpers
48PHN	UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (21-22) Seats
48RLX	CUSHION, SEAT 15" Depth
48RRA	UPHOLSTERY, SEAT, STITCHING Single

BODY FEATURES

48HAC	WINDOW, ENTRANCE DOOR Laminated, Clear, with Single Piece Glass
49AMJ	ALARM, BACKING {Ecco #575} 107 dB
49AMT	CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses
49BGJ	FLASHER SYSTEM Omit; To be Used for Multi Functional School Activity Bus or Commercial Models Only, Non Route Use
49JBU	LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light
49BCR	LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection
49CKB	LIGHT, INDIC, WARNING LIGHTS OMIT, To be Used for Multi Functional School Activity Bus, Non Route Use Only
49JBV	LIGHT, LICENSE PLATE {Sound Off/OptiLuxx} LED, with Mounting Gasket
49JBW	LIGHT, STEP {Sound Off/OptiLuxx} 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door
49EYH	LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High
49ZNC	LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange
49JBS	LIGHTS, CLUSTER {Sound Off/OptiLuxx} Oval, 4 Internal LEDs per Light; Amber Front and Red Rear
49BYZ	LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber
49MTD	LIGHTS, DIRECTIONAL, SIDE {Sound Off/OptiLuxx} Amber, Rectangular LED Armor Type, (2) Mounted at 1st Window Section and (2) Mounted Over Rear Wheel Pocket, Between 2nd and 3rd Rub Rail
49JEK	LIGHTS, DOME LED, Rectangular Recessed Type, Two Full Rows, for 34'02", 34'11", 35'08" Body Lengths
49ESC	LIGHTS, DOME, DRIVER (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch
49JED	LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear
49ZNN	LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units 30 Foot or Longer
49BYT	LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red
49ZNG	LIGHTS, STOP & TAIL ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Round LED, Red, with Flange
49BGH	LIGHTS, WARNING Omit All; To be Used for Multi Functional School Activity Bus, Non Route Use Only
49AWV	SPEAKERS AND WIRING (8) Flush Mounted In Light Bar
49AJY	STOP ARM, FRONT Omit

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
49BSL	SWITCH, DOME LIGHTS, DIMMER for All Passenger Dome Lights
49AMY	SWITCH, REAR DOOR BUZZER for Emergency Door
49BTR	WIRING MOD, DOME LIGHTS Mounted in Ceiling
49EGM	MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco Mini Hawk-Eye} Black, Heated <u>Includes</u> : MIRROR MOUNT Attached to Body with Metal Backing Plates
49EGC	MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners
49DNB	MIRROR, REAR VIEW, EXTERIOR {Rosco AccuStyle} Black, Motorized Head, Heated, Breakaway Bracket
49ENK	VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield
49GDS	COMPARTMENT ABOVE DRIVER Left of the Driver <u>Includes</u> : COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type
49JGJ	FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle
49JGN	FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat
49JGW	KIT, BODY FLUID National Standard, Poly White Box
49EUB	KIT, FIRST AID Metal; 24 Unit, Spec State
49MZV	LATCH, COMPARTMENT Locking, for Overhead Storage Compartment
49JEY	LOCATION, BODY FLUID KIT on Bulkhead
49GCH	LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws
49GDG	PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light
49GLP	REFLECTORS, REAR (2) 3", Red, Mounted with Screws
49GLM	REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted with Screws
49GLA	REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third Rub Rail From the Top
49GLG	REFLECTORS, SIDE, REAR (2) 3", Red, Mounted with Screws
49GED	SAFETY TRIANGLES Warning Reflectors, Mounted on Floor Between Driver Seat and Drivers Crash Barrier/ Stanchion/Partition
49GUB	CUTTER, SEAT BELT {TIE TECH Safecut} for Cutting Seat Belts
49JGE	CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver
49JAC	DEF FILLER DOOR with Non-Locking Latch
49GUK	FENDERS, RUBBER, REAR (2)
49MZS	FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position
49CKT	FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only
49GUM	INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel
49GVC	MUD FLAPS, REAR WHEELS (2) Rubber

Vehicle Specifications
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Code</u>	<u>Description</u>
49MUC	SIGN, DESTINATION, FRONT Omit
49MUD	SIGN, DESTINATION, REAR Omit

Services Section:

WARRANTY

40126	WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later, CTS-3304H
40YET	SERVICES, TOWING Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident
40CYY	SRV CONTRACT, ENTRANCE DOOR 3 Year/Unlimited Miles, Entrance Door Policy
40YGC	SRV CONTRACT, EXT VEH COVERAGE To 24-Month/50,000 Miles (80,000 km), Covers 100% Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or Corrosion of Cab/Cowl Structure and Paint

BODY FEATURES

49GVN	WARRANTY 5-Year, Limited
	49GVN Warranty 5-Year, Limited is an International warranty only. It does not apply to any after-market parts.
	40YGC Warranty: Longhorn Bus will cover the warranty for 2 yrs./unlimited mileage. (International will cover the first 50K miles. Longhorn Bus will cover 50K+ miles, up to the ending of the Two-year term, per current Texas School Bus Specifications.)
	AC - 136KBTU BERGSTROM - FRONT & REAR INWALL W/MID EVAPS (FACTORY INSTALLED DASH AC) LHB INSTALL
	DOT INSPECTION
	PRE DELIVERY INSPECTION CE MODEL
	SET GOVERNOR SPEED 75 MPH
	WEIGHT SLIP

Financial Summary
2026 CE SCHOOL BUS (PB110)

August 21, 2025

<u>Description</u>	(US DOLLAR)	<u>Price</u>
Net Sales Price:		\$161,502.00

Prices are good for 30 days from the date of this proposal. Price does not include Buy Board fee of \$800 per purchase order, please add if applicable for Buy Board contract 722-23.

PRICE PER BUS: \$161,502.00

ESTIMATED DELIVERY TERMS: 300-365 Days from receipt of a purchase order. Longhorn Bus Sales will not be held responsible for material shortages or delays due to any global pandemic or any other reasons outside of our control, that of the represented OEM (IC Corp) or third-party vendors used to complete a customers' bus order. **Any buses ordered will be subject to any and all applicable surcharges at the time of build, due to market volatility. Any applicable surcharges will be the buyers responsibility.** A bus order may be delivered without OEM or third-party products (i.e., A/C, GPS, two-way radios, camera surveillance equipment, etc.), and any such items will be installed immediately upon availability. Due to industry constraints, quote pricing may fluctuate.

Potential shortages/delays will not hold up invoicing and/or payment. Instructions for payment of invoices will be provided upon invoicing. Please AVOID wiring any funds to previous accounts. Due to new ownership by Holt Truck Centers, please contact Ashley Schrader at 713-631-9306 for payment instructions.

OPTIONAL ITEMS TO CONSIDER (Not included in above pricing)

(*) Bendix Wingman Fusion 3.0 - \$2,975.00 per bus

(*) Previously the Bendix Wingman Advance collision mitigation system was a standard feature on the IC Bus Product. This system is being discontinued by Bendix. The new Bendix Fusion 3.0 collision mitigation system with Pedestrian Autonomous Emergency Braking is now available as an option for customers who are interested in our most advanced safety system yet.

By signing this document in acceptance of an order, the customer acknowledges that all equipment listed within this document is correct. Longhorn Bus Sales will not be responsible for any miss-built units. Any changes to what is listed herein, may result in additional charges to an order.

Signing this proposal will not be accepted in place of a purchase order. A purchase order is required to initiate any new bus order. If your agency does not use purchase orders, please sign this proposal and prepare a written letter of intent noting the need to place your order for the specific equipment desired.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

**This proposal is not binding upon the seller without
Seller's Authorized Signature**

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.