

RELOCATED SHELVING.  
COORDINATE WITH  
OWNER AND ARCHITECT

IN SAME  
LOCATION AS  
EXISTING TO  
PROVIDE DIMMING

**LIBRARY**

|     |    |
|-----|----|
| 163 |    |
| EX  | EX |
| EX  |    |

RELOCATED SHELVING.  
COORDINATE WITH  
OWNER AND ARCHITECT

OPERABLE G  
BASIS OF DES  
MODERNFOL

23' - 6"

135.00°

PROVIDE ALTERNATING  
KICKERS UP TO  
DECK/STRUCTURE BOTH  
SIDES OF DOOR FRAME

**GATE**

|     |    |
|-----|----|
| T-2 |    |
| PT1 | EX |
| EX  |    |

PROVIDE FILM (FL1) ON  
EXISTING BORROWED LITE.  
**BASIS OF DESIGN: SOLYX;**  
**PATTERN TO BE SELECTED**  
**BY ARCH.**

PROVIDE NEW  
DIMMING SWITCH

111.1

A1

**OFFICE**

|       |    |
|-------|----|
| 111.1 |    |
| PT1   | EX |
| EX    |    |

RELOCATED  
BORROWED  
LITES

5' - 4"

6' - 0"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

3' - 4"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

2' - 6"

6' - 0"

1' - 6"

A1.2

20' - 0"

4

A2.1

A